Ρ	ro	jec	t:
		·	

Fixture Type:

Location:

Contact:

Wall mounted • Damp location listed PROGRESS LED

Description:

These fixtures feature a modern repeating circular frame. Etched opal glass shades are seamlessly secured to provide a clean, contemporary look to your home. The modern LED source delivers crisp, high quality lighting that is the perfect choice for both general and task lighting.

Specifications:

- Brushed Nickel (-009) (plated)
- Steel construction
- Etched Opal glass diffuser
- These fixtures have a pleasing familiarity within a modern repeating circular frame
- Etched opal glass shades are discreetly secured with no visible fittings.
 The modern LED source delivers crisp, high quality lighting that is the perfect choice for both general and task lighting in bath or powder rooms
- Part of these offering high style and design.
- Can be mounted vertical or horizontal.
- 624 lumens 66 lumens/watt
- 3000K color temperature, 90+ CRI
- Dimmable to 10% brightness (See Dimming Notes)
- Backplate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR[®] qualified

Performance:

Number of Modules	3	
Input Power	9w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW	624/66 (LM-79)	
ССТ	3000 K	
CRI	90+	
Life (hours)	60,000 (L70/TM-21)	
EMI/RFI	FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30° C	
Warranty		
Labels	cCSAus Damp location listed	
	ENERGY STAR [®] qualified	

Images:



Dimensions:

Width: 24" Depth: 4-5/8" Height: 5-1/2" H/CTR: 2-3/4" (vertical) Wall mounted • Damp location listed PROGRESS LED



This light is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

