



PREPARATION before INSTALLATION:

1. If an existing fixture is being replaced, remove it and note to which wire in the outlet box the original fixture was attached.
2. Before discarding the carton, double-check the packaging to make sure all parts have been found.
3. This fixture was designed to be mounted on an octagon outlet box. The box must be securely mounted to the structure of the building.

IMPORTANT:

1. **WARNING** - Disconnect power before relamping or wiring the fixture. Turn off the entire electrical circuit to which the lighting fixture is attached.
2. Installation and maintenance of this fixture should be completed by a licensed electrician.
3. Failure to install the fixture correctly could result in serious injury or death.
4. Read all instructions before starting installation.

INSTALLATION STEPS:

1. Loosen the screws in the iron fittings to adjust the height of the cable, and tighten the screws to fix the height of the cable.
2. Secure the mounting plate to the junction box using mounting screws.
3. Connect the incoming and outgoing wires using wiring caps. (Note: Connect the black wire to the black (live), the white wire to the white (neutral), and the ground wire to the ground pole.) Do not expose the wires when wiring.
4. Secure the top plate to the mounting plate with screws.
5. Install the bulb on the lamp holder.
6. Put the lamp head into the glass, and use the gap cover on the lamp head to rotate slowly into it; Pull up the lamp head and slowly lower the other flat iron cover, and then lock the iron on the flat iron cover into the thread joint on the gap cover of the lamp head.
7. Turn on the power to check whether the bulb is working properly. The installation is complete.