

ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING:

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF
POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

1. Push the plastic wall anchor in the holes pre-drilled in the ceiling in place.
2. Attach the backplate to outlet box using
2 outlet box screws upwards.
3. Make wire connections:

--Attach ground wire to house ground wire
using a wire nut or attach them to the
cross bar with a green ground screw.

--Attach white wire from light to white wire
from power source with a wire nut.

--Attach black wire from light to black
wire from power source with a wire nut.

Observing: positive wire with positive wire,
negative wire with negative wire, ground
wire with ground wire.

4. Tuck the wire connections neatly into the outlet box.
5. Attach the canopy to the ceiling and let the
2 mounting screws pass through the 2 pre-drilled
holes on the canopy and fix it in place by ball nuts.
6. Place the glass shade onto the socket and secure
it with socket ring.
7. Install bulb.(not included) (Please do not exceed
the maximum capacity which is recommended on
the fixture.)
8. Turn on the power at fuse or circuit box.

