

5" SHALLOW CEILING RECESSED HOUSINGS

5" MEDIUM BASE REMODEL HOUSING

For complete fixture, order housing with trim.

Remodel Air-Tight IC



P1841-ICAT

Ceiling opening: 5-1/2"
Recessed depth: 5-3/8"
Pryouts: 1/2"

P1841-ICAT REMODEL WITH E26 SOCKET, IC RATED, AIR-TIGHT HOUSING

- Rated for direct contact with insulated ceiling
- Adjustable housing to accommodate ceiling thickness 1/2" to 1-1/2"
- Meets ASTM-E283 air flow requirements
- Use with compatible items only



5" LED REMODEL HOUSING

For complete fixture, order housing with trim.

Remodel Air-Tight IC



P1841-LED

Ceiling opening: 5-1/2"
Recessed depth: 5-3/8"
Pryouts: 1/2"

P1841-LED REMODEL, IC RATED, AIR-TIGHT HOUSING

- Rated for direct contact with insulated ceiling
- Adjustable housing to accommodate ceiling thickness 1/2" to 1-1/2"
- Meets ASTM-E283 air flow requirements
- Use with compatible LED items only. Visit progresslighting.com.



TRIM FOR P1841-ICAT

6-1/2" outside diameter.. Can also be used with P851-ICAT



SHALLOW STEP BAFFLE

Damp location listed.

P8475-28 Satin White

Lamp: PAR30/R30, 50w max.

Compatible with **P851-ICAT** and **P1841-ICAT**.