



- Top-Lift Design – Easy-access water bucket for effortless removal and replacement.
- Large 18-Pint Bucket – Holds more water to reduce the number of trips for emptying.
- Built-In Pump – Includes a quick-connect drain hose for convenient continuous operation.
- Quiet Performance – Low-noise system designed for a quieter home environment.
- Reusable Filter – Removable, washable filter helps maintain clean air and smooth performance.
- Compact, Elegant Design – Fits seamlessly into any room without taking up extra space.
- Portable by Design – 4 easy-roll casters included make relocation effortless.



TopLift™ Water Bucket

Ergonomic design with large handle for easy lifting and draining.



Large 18-Pint Water Bucket

Hold more water and save trips of emptying water



Reusable Filters

Washable filter helps to reduce bacteria, odors and particles.



Built-in Pump

Flexible draining option that pumps the water up to 16 ft.

Hisense TopLift™ 50 Pint Dehumidifier with Water Pump

Experience smarter comfort with our innovative dehumidifier, designed to make moisture control easier than ever. The top-lift design provides quick, effortless access to the large 18-pint water bucket, while the built-in pump with quick-connect hose lets you enjoy hassle-free continuous operation. Engineered for quiet performance, it runs smoothly in the background without disrupting your home. A reusable, washable filter keeps the air fresh and the unit running efficiently. With its sleek, compact design and four easy-roll casters, this dehumidifier blends seamlessly into any room while offering the portability you need.

TECHNICAL SPECIFICATIONS


Model #	HD5026TLP
Performance	Performance
Dehumidification (Pints/24 hours)	50
Coverage	Up to 4500 sq ft
Refrigerant	R-32
Noise Level in dB(A)	45-48 dB(A)
General Features	
Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	Yes
Display Type	Dimmable LED
Continuous Run	Yes
Auto Dry	Yes
Manual Setting	30% ~ 80%
Timer	Yes, 30 minutes to 24 hours
Fan Speeds	3 Speeds (High, Med, Low)
Auto Bucket Shutoff	Yes
Removable Filter	Yes
Washable Filter	Yes

Electrical	
Voltage / Freq / Amps	115V / 60Hz / 7.6A
Power Cord Length	6 feet
Accessories	
Quick Connect Hose	Yes, included (9mm diameter)
Length of Included Pump Hose	16 feet
Max Pump Discharge Height	16 vertical feet
Approvals	
Safety	UL
Energy	Energy Star
Shipping	
Unit Dimension WxHxD (mm)	430x485x280
Net Weight (kg)	18.3
Unit Dimension WxHxD (inch)	16.9x19.1x11
Net Weight (lbs)	20.2
Warranty/UPC	
Parts & Labor	2 Years
UPC	

Note:
*: Rated Amps(A) / accorded UL 60335 Safety

Product Images

Control Panel



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2020 Hisense USA, All rights reserved

Hisense USA Corporation
7310 McGinnis Ferry Road, Suwanee, GA, 30024
1-888-935-8880
www.hisense-usa.com