



FT-293 Condotti Obelisk Fountain (5 pieces)

COMPONENTS AND PARTS LIST


Revised July 12, 2016




FT-269H
24"x24"x15"
392 lb




P-713
40"x40"x25.25"
500 lb



FT-281B
11.5"x11.5"x9.75"
57 lb



FT-281A
10.5"x10.5"x37"
175 lb



FT-291C
6.75"x2.25"x5.75"
3 lb



Pump Kit Parts List

- PK800 pump (1)
- Approx. 12" length of 1/2" black non-kink tubing (1) **
- Approx. 2" length of 5/8" clear vinyl tubing (1) **
- Approx. 2" length of 3/4" clear vinyl tubing (1) **
- #10 compression stopper (1)
- #7 Drain Stopper
- Wedges (2)
- Hose clamps (2)
- 4mm Allen wrench (1)
- Note – Hose clamps may be used as flow restrictor
- **Tubing will be pre-assembled

Tools you will need

- Level
- 
- 4mm Allen wrench
- (included) 

**This fountain uses cover
FTNCOV-XLG**



FT-269I
8.25"x9"x2.5"
13 lb

FT-293 Condotti Obelisk Fountain

(5 pieces)

Revised August 24, 2015

ASSEMBLY INSTRUCTIONS

Two people are required for the installation of this fountain!

1. Make sure you are assembling your fountain on a level surface capable of holding a minimum of 650 pounds with approximately a 5 square foot footprint.
2. Place the base (FT-269H) into position where the fountain will be installed, ensuring that it is level.
3. Place the urn (P-713) on top of the base, ensuring that it is centered and level.
4. Feed the pump cord through the large, centered hole in the urn and down through the base.
5. Pull the pump cord all the way through the bottom of the base and out the access window leaving enough cord length in the bowl to work with the pump.
6. **See enclosed stopper assembly instructions and complete before continuing.**
Place the pump cover (FT-281B) inside (P-713) over the pump, ensuring that it is centered and level.
7. Connect the $\frac{3}{4}$ " end of the tubing assembly to the pump outlet.
 - a. Note: If you wish to use one of the hose clamps as a flow restrictor, you must install it on the tubing at this point.
8. Place a hose clamp over the $\frac{1}{2}$ " end of the tubing assembly and attach to the pipe protruding out of the bottom of the water feature obelisk (FT-281A).
9. Tighten the hose clamp to ensure a good seal.
10. Place the pump cover door (FT-281C) in the pump access opening of the pump cover.
11. Place the access window cover (FT-269I) in the access window at the base of the fountain.
12. Fill the basin with approximately 25 gallons of water.
 - a. NOTE: Do not run fountain without sufficient water. If the pump is allowed to run dry, it can damage the pump.

WINTER CARE AND GENERAL FOUNTAIN INSTRUCTIONS

- W I N T E R C A R E -

Fountain bowls/tops and other fountain components, which collect water, should not be left outside in the winter since any component, which fills with water and freezes may crack. Likewise components such as pedestals, which remain in a basin, filled with water, which then freezes, may also crack or crumble. Ideally, therefore, a fountain should always be stored indoors or in a dry protected place such as a covered porch away from the elements. However, if a fountain must be left outside:

(1) Remove pump, rubber stoppers, drainpipes, finials, and other small components for storage indoors. Note that stoppers or drainpipes are removed to allow drainage in the event water accumulates in any basin.

(2) Raise fountain base from ground with wood strips so that base will not freeze to the ground surface.

(3) Cover or wrap the fountain with burlap or other absorbent material (old blanket or towel) and then cover securely with plastic, making sure that water will not accumulate in the basin or other fountain component and freeze;

(4) Check fountain periodically to insure that plastic is secure and water is not accumulating in any fountain component.

- G E N E R A L F O U N T A I N T I P S -

Install fountains on a level surface. You will need a properly grounded 110-volt (AC only) GFCI protected receptacle near the fountain for your pump. All pumps are submersible and must be completely underwater to function properly. Test all pumps and adjust to full output prior to assembly. It is not recommended that fountains be placed directly on grass or dirt. Position the channel opening at the base

All of our cast stone is proudly



Made in USA

of each fountain toward the electrical outlet to be used since the pump cord will be threaded through this opening.

For more Campania product information visit www.campaniainternational.com