
## HR-D413

# 4" Low Voltage Downlight Trim

# **WAC LIGHTING**

### Responsible Lighting®





# Fixture Type: Catalog Number: Project: Location:

#### **PRODUCT DESCRIPTION**

Slotted aperture trim with black interior. Used for controlled highlighting or drama from a small aperture. For use with HR-8400 series low voltage housings.

#### **FEATURES**

- · Slot trim, 35° adjustment from vertical recessed downlight
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Handles surfaces up to 3/4" thick
- · 5 year WAC Lighting product warranty

#### ORDER NUMBER

Model # Finish

HR-D413 WT White

Model # Finish

HR-D413 - WT

Example: HR-D413-WT

#### **SPECIFICATIONS**

**Construction:** Durable die-cast aluminum construction. Three heavy gauge retention clips firmly hold trim to housing.

**Lamp:** Utilizes LED or Halogen 12V MR16 lamps (order separately). 50W or 75W maximum, see individual housing for wattage rating.

**Finish:** Abrasion resistant powder coat painted or plated metal finish. Available in White (WT).

Standards: UL & CUL Listed, Suitable for damp locations

#### **ACCESSORIES**

		AMB	Amber	LENS-16-UVF	UV Filter		
		<b>BLU</b> Blue		LENS-16-FR	Frosted Lens		
LENS-16- Color Lei		GRN	Green	LENS-16-SPR	Spread Lens		
		RED	Red	LENS-16-BEL	<b>Beam Elongating Lens</b>		
		YEL	Yellow	LENS-16-HCL	Honeycomb Louver		

4" Low Voltage Housings (Required)			Model Voltage		Transformer	Output	Installation	Rating	
T EOW VOILINGE THE	4½"	5%6"   8 %6"	HR-8402E	VOICE	120V	Electronic		New Construction	Non-IC
	65/6"	61½6"	HR-8402HL*		120V	Magnetic	12V, 75W max	New Construction	Non-IC
	7%6"	10%"	HR-8403	H HF	120V 277V	Magnetic	12V, 50W max	New Construction	IC Airtight
	5½"	61½s" [ ] [ ] [ ] [ ] [ ] [ ] [ ] [ ] [ ] [	HR-8402	H HF	120V 277V	Magnetic	12V, 50W max	New Construction	Non-IC
	4½" 4½" 13¾6"				120V	Electronic	12V, 50W max	Remodel	Non-IC
	41/6" 119/6"	HR-8401	H HF	120V 277V	Magnetic	12V, 50W max	Remodel	Non-IC	

\*Not Compatible with HR-D418 or HR-D418-S Non-IC housings require 3" of clearance from insulation on all sides. Accommodates ceiling thickness of up to ¾" for remodel & ¾" for new construction.

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585