

Project: _____

Fixture Type: _____

Location: _____

Contact: _____

Ceiling cord mounted • Damp location listed



Specifications:

Description:

One-light LED pendant features designer oriented details. Brushed Nickel finish with polished white interior. 3000K, 90+ CRI, 623 lumens. Title 24 compliant.

Construction:

- Brushed Nickel (-09) (plated)
- Steel construction
- Glass: Aluminum Shade shade
- LED Module is replaceable (Part # 93054049)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- CA Title 24 compliant
- Canopy covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied

Performance:

Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30
Max. Operating Temp	30
Labels	cCSAus Damp location listed ENERGY STAR® qualified

Images:



Dimensions:

Diameter: 6-1/2"
Height: 8-7/8"
Overall ht. w/cord: 130"

Catalog number:

Base	Finish	Color Temp	CRI
	Brushed Nickel	3000K	90 CRI



Dimming Notes:

This collection designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.
