## Hisense







- Bucket full indicator prevents overflows
- 3 Modes Auto, Continuous, Manual
- 3 Fan Speeds (High, Low, Auto)
- Low-temperature Operation (38°F)



### **Low Noise Airflow System**

High-performance centrifugal fan ensures quiet operation at 45 dB(A) with the fan set on "Low".



### **Energy Efficient**

Energy Star means it's more energy efficient and helps reduce your utility bill.



### **Filter Indicator**

Washable filter helps to reduce bacteria, odors and particles.



### Warranty

2 Years Parts & Labor.

## Control Humidity – Helps keep your home conveniently dry, fresh, and quiet

The Hisense AHD5024K1W Energy Star 50 Pint 3-Speeds Dehumidifier quietly collects water into the slide-out internal bucket or can discharge the water via connecting a garden hose (not included) through the side of the cabinet. Reliable and eco-friendly, this dehumidifier can operate at temperatures as low as 38°F.

Three operating modes (manual, continuous, and auto dry) and the very low sound level make this a versatile choice. Additional features include a programmable 24-hour on/off timer, adjustable humidistat, and full-tank alert/shutoff.

# Hisense



### **TECHNICAL SPECIFICATIONS**

TECHNICAL SI ECH ICATIONS	
Performance	Performance
Dehumidification (Pints/24 hours)	50
Coverage	Up to 4500 sq ft
Refrigerant	R-32
Noise Level in dB(A)	45-48 dB(A)
General Features	
Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	Yes
Display Type	Dimmable LED
Continuous Run	Yes
Auto Dry	Yes
Manual Setting	30% ~ 80%
Timer	Yes, 30 minutes to 24 hours
Fan Speeds	3 Speeds (High, Low, Auto)
Auto Bucket Shutoff	Yes
Garden Hose Connection	Yes, garden hose not included
Washable Filter	Yes

Electrical	
Voltage / Freq / Amps	115V / 60Hz, 7.2A* / 4.9A
Power Cord Length	6 feet
Approvals	
Safety	UL
Energy	Energy Star
Shipping	
Unit Dimension WxHxD (mm)	384 x 629 x 272
Net Weight (kg)	17.6
Unit Dimension WxHxD (inch)	15.1 x 24.8 x 10.7
Net Weight (lbs)	38.8
Warranty/UPC	
Parts & Labor	2 Years
UPC	810088366406

#### Note.

## **Product Images**

### **Control Panel**



### **2 Draining Options**

Bucket conveniently located on front with handle for easy emptying



Use a garden hose (not included) for continuous draining to avoid emptying the bucket.



<sup>\*:</sup> Rated Amps(A) / accorded UL 60335 Safety