RR9ICA


6" IC Shallow Remodel Housing, Airtight

PROJECT INFORMATION:


Date:

i ioject maine.		
Fixture Type:		

DIMENSIONS







PRODUCT SPECIFICATIONS

Housing Features: Remodel shallow airtight IC housing with integral thermal protector guards against improper lamping. Single wall construction. Adjustable socket bracket allows the use of different lamp types and sizes as well as proper and consistent positioning.

Lamp: 120V, 75W max, A19 / A21 / R30 / PAR30 / PAR30L type base.

Lamp Holder: Medium base socket.

Trim Ring: Polycarbonate trim ring, metal trim ring, designed to conceal ceiling cut-out.

RR9ICA meets with California Title 24 requirements.

INSTALLATION

Junction Box: Pre-wired junction box provided with 1/2" and 3/4" knockout through branch wiring, maximum (8) No. 12 AWG branch circuit conductors (4 in, 4 out). Junction box provided with removable access plates.

Mounting: Four remodel clips secure housing and accomodate various ceiling thickness.

Mounting Frame: Stamped galvanized steel for corrosion resistance.

Labels: • U.L. listed for damp locations.

• U.L. listed for feed through.

CATALOG NUMBER

Example: RR9ICA - ELM30W

See trim page for variety of trims available

