

42" Ceiling Fan

Project Name: _____

Location: _____

Type: _____

Qty: _____

Comments: _____



Dimensions

Downrod	A	B	C	D
1.00 OD X 4.50	13.75	11.00	8.00	5.90

Available Finishes

Finish	Fixture	Glass	Blade 1	Blade 2
Matte White			MATTE WHITE	MATTE WHITE

Product Information

Blade Finish	Matte White/Matte White
--------------	-------------------------

Airflow, Power and Efficiency

Speed	RPM	CFM	CFM/ Watt	Amps	Watts
Low	200	3897	82	.4	48
Med	150	2997	119	.3	25
High	96	1822	177	.2	10

Specifications

Number of Blades	5
Blades Included	Yes
Blade Pitch	14 Degrees
Blade Sweep	42"
Blades Reversible	Yes
Blade Material	WOOD
Optional Blades Available	No
Downrod 1	1.00 OD X 4.50
Primary Control System	Pull Chain
Remote Included	No
Wall Control Included	No
Low Ceiling Adaptable	No
Lead Wire Length	78.00"
Motor Size	153MM X 15MM
Motor Type	AC

Safety Listings & Certifications

Safety Rated	Dry
Warranty	

Installation

Installation requirements	The electrical junction box and support structure must be securely mounted and capable of reliably supporting a minimum of 50 pounds. Use only ETL listed electrical junction boxes marked "For Fan Support"
Electrical Requirements	120V 60Hz AC
Minimum Distance Between	

Notes:
1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

42" Ceiling Fan

Project Name: _____

Location: _____

Type: _____

Qty: _____

Comments: _____

Finish	Fixture	Glass	Blade 1	Blade 2
Olde Bronze			WALNUT	CHERRY
Brushed Nickel			WALNUT	SILVER

Bottom Of Fan Blade To7.5 feet

Floor

Control Options

Product ID	Descr
	Universal Remote Control
	4 Speed Fan Slide Control
	4 Speed Fan Slide Control
	4 Speed Fan Slide Control
	Limited Function Cooltouch
	Wall Control System L-Function
	4 Speed Rotary Switch 10 AMP

Notes:
1) Information provided is subject to change without notice.
All values are design or typical values when measured under laboratory conditions.
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.