


User Manual

Brass Toggle Switch





WWW.OZARKE.COM

Thank you for shopping with Ozarké, we really appreciate your business. Our goal is to provide an excellent customer service before, during and after delivery. We've included a guide on how to install this light, should you require additional assistance please feel free to email us and one of our customer service reps will reach out to assist you.

You can reach us via email at info@ozarke.com or via phone at +1-(800) 604-7271

BEFORE YOU GET STARTED

When working with electrical wiring, follow these safety instructions to prevent injury or damage:

1. Turn off the power: Before starting any work, turn off the power to the area you will be working in.
2. Use appropriate tools: Only use tools designed for electrical work and in good condition.
3. Wear protective gear: Wear safety glasses, gloves, and other protective gear as necessary.
4. Test for power: Use a non-contact voltage tester to check for electrical current before touching any wires.
5. Avoid wet conditions: Do not work with electrical wiring in wet or damp conditions.
6. Keep a safe distance: Stay away from exposed wires or electrical components.
7. Seek professional help: Consult a qualified electrician if you are unsure about any aspect of electrical wiring or encounter any problems.



WARNING!

1. Install and use only in accordance with applicable electrical codes and regulations.
2. If you are unsure about any part of these instructions, consult a licensed electrician.
3. Use this device only with copper or copper-clad wire.
4. To avoid fire, shock, or death: turn off power at the circuit breaker or fuse, and verify that power is off before wiring.



Brass Toggle Switch

Instructions

NOTE: Terminal screws accept up to #12 AWG copper or copper clad wire. Push-in terminals accept #14 solid copper wires **ONLY!** For circuits with #12 AWG solid copper or copper clad wires, use terminal screws instead.

1. Wire the Switches (refer to the wiring diagram)

Side-Wiring Method:

- 1- Strip approximately 3/4 in. (1.9 cm) of insulation from each wire.
- 2- Form a clockwise 3/4 turn loop and place it under the terminal screw.

Switch A (line side):

- Connect the line hot (black) wire to the common terminal (black screw).
- Connect the two traveler wires to the traveler terminals (brass screws).
- Connect the green or bare ground wire to the green hex-head screw.
- Tighten all screws to 14 lbf-in (1.6 N·m).

Switch B (load side):

- Connect the load (black) wire to the common terminal (black screw).
- Connect the same two traveler wires to the traveler terminals (brass screws).
- Connect the green or bare ground wire to the green hex-head screw.
- Tighten all screws to 14 lbf-in (1.6 N·m).

2. Mount the Device

Secure the switch(es) in the wall box with the screws provided, then install the wall plate.

3. Restore Power

Turn the circuit breaker or fuse back on. Your installation is complete.

