


InvisiLED® Pro Outdoor

24V Outdoor LED Tape Light

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Pro Outdoor is great for any and all outdoor accent lighting applications. Double insulated silicon encasement and distinct electrical and mechanical junctions make for a superior watertight custom system.

FEATURES

- IP-68 rated, allows for submersion up to five feet
- Power supply is UL and CUL listed
- Wet location listed
- Ultra thin profile at 1/8"
- Diodes spaced evenly at 1" on center
- Minimum run length of 1' and maximum of 28'
- May be field cut every 6" and at the end of a run
- Unique tape section connections ensure even LED spacing and no dark spots
- Four mounting options provided for different surfaces
- 80,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Flexible, silicone sealed tape light.
Indicating marks on back for field cutting

Power Supply: Remote electronic Class 2 transformer.
120VAC 50/60Hz input, 24VDC 100W output.

Light Source: 12 LED diodes per foot. Runs on 24V at 3.5W per foot.

Operating Temperature: -4°F – 122°F (-20°C – 50°C), relative humidity 95%.

Standards: UL & CUL Listed. UL (E204239) wet location certified.

FIXTURE PERFORMANCE

Color	Color Temp	Watts/ft	Lumens/ft
White	3500K	3.5	220

POWER SUPPLY

EN-O24100-RB2-T 24VDC/100W Class 2 LED transformer

TAPE LIGHT ACCESSORIES

LED-TO24-IC	Joiner cables
LED-TO24-X	4 way "X" connector
LED-TO24-Y	3 way "Y" connector
LED-TO24-EC	End cap
LED-TO24-C1	Mounting clip 1 (10 per pack)
LED-TO24-C2	Mounting clip 2 (10 per pack)
LED-TO24-C3	Mounting clip 3 (10 per pack)
LED-TO24-CH	Clear channel

For full descriptions and specs of Power Supply and Accessories see next page.

ORDER NUMBER

Model #	Length	Color			
LED-TO2435	1 1 foot	WT White	3500K	3.5W / ft	
	5 5 feet				
	10 10 feet				


Model # Length Color
LED-TO2435 - -









Example: **LED-TO2435-1-WT**

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585

POWER SUPPLY		Model #	Input	Output	Dimensions	Description
Remote Class 2 DC Transformer		EN-O24100-RB2-T	120V-277V AC	24V DC/96W	11 ⁷ / ₁₆ " × 4 ¹ / ₈ " × 1 ¹⁵ / ₁₆ "	6' lead wire included. Requires a minimum load of 1W. Max run 100W: 28'

TAPE LIGHT ACCESSORIES		Model #	Dimensions	Description
Joiner Cable		LED-TO24-IC6 LED-TO24-IC12 LED-TO24-IC72 LED-TO24-IC120	6" 12" 72" 120"	Connects two sections of InvisiLED® Classic Outdoor.
4-Way "X" Connector		LED-TO24-X	wires: 5" each connectors: 3/4" each	"X" connector has one male and three female connectors and can be used to easily customize your design layout.
3-Way "Y" Connector		LED-TO24-Y	wires: 5" each connectors: 3/4" each	"Y" connector has one male and two female connectors and can be used to easily customize your design layout.
End cap		LED-TO24-EC	5/8" × 5/8" × 3/8"	Use to terminate every run to protect against contaminants. Seal cut end with silicone after adding end cap.
Mounting Clip 1 (10 pack)		LED-TO24-C1	1 1/8" × 3/8" × 1/4"	For installation on non-flat surfaces where there is no edge contact. 2 clips per ft are recommended for straight runs.
Mounting Clip 2 (10 pack)		LED-TO24-C2	7/8" × 3/8" × 1/4"	For installation on non-flat surfaces, allows for contact on one edge. 2 clips per ft are recommended for straight runs.
Mounting Clip 3 (10 pack)		LED-TO24-C3	5/8" × 5/8" × 1/4"	For installation on non-flat surfaces, allows for contact on both edges. 2 clips per ft are recommended for straight runs.
Clear Channel		LED-TO24-CH1 LED-TO24-CH5	12" × 5/8" × 1/4" 60" × 5/8" × 1/4"	Rigid, non-flexible channel for mounting to a straight, solid surface.