

① light arm 3PCS  
 ② light arm 6PCS  
 ③ lock nut & teeth lock washer  
 ④ connected plate 1PCS  
 ⑤ bottom cover 1PCS  
 ⑥ end cap 1PCS  
 ⑦ splicing connector 2PCS  
 ⑧ hanging tube 1PCS  
 ⑨ hanging tube 1PCS  
 ⑩ chain 1PCS  
 ⑪ canopy 1PCS  
 ⑫ cap nut 2PCS  
 ⑬ cylinder tube 9PCS  
 X 1PCS  
 X 1PCS  
 X 3PCS  
 X 3PCS  
 X 3PCS  
 X 3PCS

position of the light arms

light arm ①

light arm ②

1. Install the light arms on the connected plate ④ with lock nut & teeth lock washer ③.

2. Connect all the wires by parallel with connectors ⑤ (all live line-L use one connector, and neutral Line-N use another connector), close the bottom cover ⑤ with end cap ⑥.

3. Let the wire go through the hanging tube ⑧ and ⑨, rotate to install to the fixture.

4. Hang the fixture to the canopy ⑪ with chain ⑩, let the wire go through the chain ⑩ and canopy ⑪.

5. Install the bracket to the ceiling junction box with screw ⑭.

6. Connect the wire to your home line with cap connector ⑮.

7. Install the fixture to the bracket with cap nut ⑫.  
 8. Put the cylinder tube ⑬ on top of bulb holder, install the bulb ⑯.

**Please read carefully before installation!!!**  
**Note : Please make sure that the electricity is powered off during installation !**  
**Only a professional electrician should install this kind of product !**