

INSTALLATION INSTRUCTIONS

FOR LED Pendant Light

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT ! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DO DISJONCTEUR

PREPARING FOR INSTALLATION (Fig. 1)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.

SUGGESTED INSTALLATION (Fig. 1)

3. Secure the thread rod (I) to the hex nut (J).
4. Put the cover (H) onto the fixture body (D) through the thread rod (I), and secure it by the nut (G).
5. Remove the two mounting screws (DD) from the side of the canopy (A) and remove the mounting plate (BB).
6. Press the wire restraint (B) on the canopy (A) to adjust the cable (C) to desired length. Press the wire restraint (F) on the canopy (A) to adjust the fixture wire (E). The fixture wire (E) should be longer than the cable (C).
7. Secure the mounting plate (BB) to the outlet box (not included) with the outlet box screws (CC). Tighten until snug.

CONNECTING THE WIRES (Fig. 2)

8. Connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate (BB) using the green screw (AA) provided. Tuck the wire connections neatly into the junction box.

COMPLETING THE INSTALLATION (Fig. 1)

9. Attach the canopy (A) to the mounting plate (BB) and secure it with the mounting screws (DD).

Your installation is now complete. Return power to the junction box and test the fixture.

IMPORTANT: Fixture should be installed by a qualified electrician to ensure proper wiring and installation.

Dimmable with ELV and/or LED compatible wall dimmer switches.

