

Installation manual

Dimensions : D19" H12" L5

Bulb Type : E12 bulb not included

Lamp Frame Weight : 9.79 LBS

Total Weight : 20.5 LBS



Thank you for choosing our product(s).

Our Company is actively involved in every step of the production.

Our product(s) are designed to be utilized for every application that graces your home or business.

We pride ourselves in providing the most prompt and courtesy service to all of the valued customers.

Please find the enclosed detailed instruction and read carefully for proper installation.



D19" H12" L5

SAFETY

WARNING: MAKE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF BY EITHER REMOVING THE FUSE OR TURN OFF THE CIRCUIT BREAKER.

CAUTION

- Before assembling the lighting fixture, please read all instructions carefully.
- All frame & crystal components are fragile, please handle with care.
- Required supply circuit : 110 - 130V/60Hz.
- Labeled wires are "L" for live wire, "N" for neutral wire, "E" for ground wire.
- Never install fixture on damp ceiling, the room should be dry and well ventilated.
- All electrical components must be installed by a licensed electrician and in accordance with the National Electrical Code and the appropriate local electrical codes.


UNPACK THE PACKAGE

Please open the box carefully and check all the items are inside the box.

01

D19" H12" L5

Frame Assembly Diagram














02

D19" H12" L5

Step 1













Please use the parts list to ensure you are not missing any parts.

PARTS LIST

Part	Picture	Description	Qty	Check list
ZA		Canopy cover 5" (Canopy part)	1	
ZB		Crossbar 4" (Canopy part)	1	
ZC		Canopy ring (Canopy part)	1	
ZD		Canopy lock (Canopy part)	1	
ZE		L47"CHAIN04P Plain Design	1	
ZF		ground wire	1	
ZG		junction caps	2	
ZH		Power Cord 12.3' /SPT-1-16# Clear/Gold	1	
P01		Chain 2.5"*0.95" (Canopy part)	1	
P02		Loop	1	
P03		Sunk Crossbar Screws	8	



03

D19" H12" L5

Part	Picture	Description	Qty	Check list
P04		rosette	1	
P05		Terminal Block	1	
P06		Square tube	4	
P07		Lamp arm	5	
P08		Nut	12	
P09		socket	5	
P10		Socket cover	5	
P11		Hickey	1	
P12		Upper lamp frame	1	
P13		Thread pipe	12	
P14		Disk	1	
P15		finial	1	

04


D19" H12" L5

Part	Picture	Description	Qty	Check list
A		710-2.5"	132	
B		711-3"	132	

D19" H12" L5

Step 1

Canopy Installation Instruction



D19" H12" L5

IMPORTANT: Test sockets with bulb before dressing the fixture.



- 1 . Attach the crossbar to the electrical box.
- 2 . Pass the lamp wire and ground wire through the loop, canopy ring and center hole of canopy cover.
- 3 . Screw 2.5" threaded pipe into the crossbar and fasten with hex-nut.
- 4 . Pull wires up through the nipple.
- 5 . Screw loop only onto threaded pipe.
- 6 . Hang the fixture on chain.
- 7 . Make the electrical connections as detailed in the drawing above.
- 8 . Secure the canopy cover with threaded canopy ring .

07

D19" H12" L5

Step 2

Frame Assembly Diagram



08

D19" H12" L5

Frame Assembly Instructions

Installation:


Please read all instructions carefully. Before you proceed to install, make sure that the power supply is turned off and remains off until installation is complete. Please note that each part has been assigned a number. Please proceed in a numerical order.

1. Hang the canopy parts (01) on the Ceiling Plate.
2. Fasten the fixture loop to hang the whole fixture(02).
3. Screw the Bulb on the Lamp Holder.
4. Follow the crystal instruction to hang the crystal.

D19" H12" L5

Step 3

Crystal Dressing Diagram



1. Hang the crystal (A) and the crystal (B) on the first circle to the fifth circle of the Lamp Frame as shown in the figure.

D19" H12" L5

Congratulations !

You are now done installing your fixture. Sit back and admire each crystal as it will become the statement piece for your room/house.

Thank you.

D19" H12" L5

Cleaning and Maintenance of Chandelier Frame

The finish on our chandelier frames and fixture frames is protected by a durable coating of lacquer. To clean, use a clean soft, dry cloth. Do not use any metal polishes, cleaners, abrasives or any substance which could remove the protective finish. Failure to follow these instructions automatically voids the guarantee.

Cleaning and Maintenance of Crystals

Wet a soft cotton fabric in clean warm water and wipe gently, then polish with a dry soft cotton fabric.

To Order Crystal Replacement Parts

Should you require replacement crystals or pins (the metal connectors attaching the crystals), contact the store where the product was purchased or contact us at the address shown on the reverse side. For ease of ordering, you may use the original crystal trimming instructions provided with this product and circle the items you wish to order, indicating the quantity by writing the number needed adjacent to the circle and faxing it to our customer service department