

LP323

Multi-color LED Headlamp






Features

- Durable ABS and rubberized compact design
- LPE optics, Multi-color COB LED area light
- Dual button intuitive mode selection
- Non-slip adjustable headband
- IPX4 waterproof rating
- Batteries included (3 AAA)

Product Warranty

The LP323 has a Limited 1-Year Warranty Against Manufacturer's Defects from time of purchase.
For warranty claims please contact us by calling 801-553-8886 or sending an email to info@simpleproducts.com

ANSI/PLATO FL1 STANDARD			
			
MODES	LUMENS	RUN TIME	BEAM DISTANCE
Spot Modes			
High+	300 lm	3h	85m
High Spot	220 lm	4h	40m
Low Spot	50 lm	6h	20m
Flood Modes			
High White	85 lm	5h 30m	20m
Low White	34 lm	8h 30m	5m
Green	51 lm	7h 30m	5m
Red	15 lm	3h	1m

Operation Instructions

Spot On/Off & Cycle Modes: Press and release the button on the right of the headlamp to turn spotlight on. Press button repeatedly to cycle through modes (Spot High/Spot Low).

High+ Mode: Press and hold the right button for 2 seconds to turn on High+ Mode.



Flood On/Off & Cycle Modes: Press and release the button on the left of the headlamp to turn flood light on. Press button repeatedly to cycle through modes (High White/LowWhite/Green/Red).

Strobe: From any mode, press and hold the left button for 2 seconds to switch to Strobe mode.



Battery Replacement

The LP323 uses 3 AAA batteries.

To replace the batteries, first locate the two plastic tabs on the sides of the headlamp. Gently push tabs outward using both thumbs to separate the battery cover from the main headlamp housing. Remove the old batteries and insert new batteries according to the (+/-) symbols in the battery tubes. For best results, we recommend using brand new alkaline batteries that are the same voltage and brand.

To re-attach the battery cover, line the plastic tabs on the main housing up to the battery cover taking note to match them in proper orientation (the LUXPRO logo on the battery cover should line up with the On/Off buttons on the main housing). Gently press the two sides together until they click into place. Check that the battery cover is secured by gently tugging on the headlamp straps while holding the main housing firm.



If you know it will be a while between uses, we suggest removing the batteries from the head lamp and storing it in a dry, protected place.