




Sandstone Lever









DESCRIPTION	PRODUCT CODE	CASE
Passage (hall/closet) Both sides always free	SS101	12
Privacy (bed/bath) Locked by push pin. Unlocked by push pin, lever turn, or emergency pin outside	SS102	12
Entry with Deadbolt (exterior door) bottom portion is passage function, locked/unlocked by deadbolt	SS107	8
Dummy (closet) Inactive, single-sided, flush mount with two wood screws	SS100	12
Double Dummy (closet) Inactive, double-sided, mounted by thru-bolts	SS100-2	12

Finishes	Door Handing	Door Thickness	Key Cylinder
11P Vintage Bronze	Handing Required	1 3/8" to 1 3/4"	5 Pin KW1
		Expansion pack available for 2 ¼" thick doors	5 Pin SC1 option

Strike Plates	Latch	Door Prep	Materials
2 ¼" x 1 ¾" full-lip radius	2 ¼" x 1" radius corner	Crossbore 2 1/8"	Solid sand-cast brass
corner standard	faceplate	Edgebore 1"	All metal parts
2 ¼" x 1 " deadbolt strike	Non-adjustable 2 3/8" or 2 3/4"	5 ½" center-to-center	
and	2 3/8" drive-in latch available		
2¾" x 1½" deadbolt strike	½" throw bolt		
	Split spindle- both sides operate independently		
	1" deadbolt throw		
	Cut resistant bolt with hard- ened steel rolling inserts		