

INSTALLATION INSTRUCTIONS FOR FIXTURE

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

ASSEMBLING THE FIXTURE (FIG. 1)

1. Shut off the power at the fuse box or circuit breaker. If necessary, remove the old fixture from the ceiling, including the existing mounting hardware.
2. Carefully remove the new fixture from the carton and check that all parts are included as shown in the illustration.
3. Attach the mounting bar (B) to the outlet box using the outlet box screws (A). The side of the cross bar marked "GND" must face out.
4. Thread the stem (H) into the coupling (G) and secure with it

CONNECTING THE WIRES (FIG .2)

5. At this point, connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate using the green screw provided. After wires are connected, tuck them carefully inside the Junction Box.
6. Attach the fixture body onto the outlet box by protruding mounting screws(C) through mounting holes on the canopy (D) and secure with ball nuts (E).
7. Install the bulbs in accordance with the fixture's specifications. **(DO NOT EXCEED THE MAXIMUM WATTAGE RATING!).**
8. Insert the glass shade (I), rubber washer (J), plate washer (K) over the stem (H) and secure with hex nut (M) until snug.
9. Insert the cap (N) over the stem (H) and secure with finial (O).

Your installation is now complete. Return power to the outlet box and test the fixture.

Fig.1

- Mounting plate
- Ground Screw
- Mounting screws (2)




Fig .2		
<p>FIXTURE WIRES Black or Smooth</p>	<p>FIXTURE WIRES White or Ribbed</p>	<p>FIXTURE WIRES Bare Copper (Ground)</p>
<p>HOUSE WIRES Black (Hot)</p>	<p>HOUSE WIRES White (Neutral)</p>	<p>HOUSE WIRES Green (Ground)</p>

