




WS-W36406

Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Flue

WS-W36406

PRODUCT DESCRIPTION

Fundamental geometry. An opaque triangular shade shelters LED light sources, providing diffused downward illumination while protecting the nighttime sky.

FEATURES

- ACLED driverless technology
- Downward illumination
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL, Wet Location Listed, IP65, ADA
Input	120 VAC, 50/60Hz
Dimming	ELV: 100-5%, TRIAC: 100-10%
Mounting	Can be mounted on wall vertically or upside down
Color Temp	2700K, 3000K, 3500K, 4000K
CRI	90
Construction	Aluminum body with silk screened diffuser

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W36406 6"	2700K	BK Black	12.1W	1000	320
	3000K	BK Black	12.1W	1000	320
	3500K	BK Black	12.1W	1000	320
	4000K	BK Black	12.1W	1000	320

Example: **WS-W36406-40-BK**

For custom requests please contact customs@modernforms.com