

## CHANDELIER FIXTURE INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

### CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

### GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections, obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

### ASSEMBLY AND INSTALLATION

- 1, Thread the loop into the nipple, then screw the metal banding and arm with the ball nut.
  - 2, Attach the Cross Bar to the Outlet Box by using 2 pcs Mounting Screws upwards. Screw the NIPPLE with the WASHER and HEX NUT to the CROSS BAR.  
Make wire connections:
    - Smooth wire (w/markings) from the light to black wire from power source.
    - Ribbed wire (w/o markings) from the light to white wire from power source
    - Attach the ground wire to the cross bar with a green ground screw. Carefully tuck wire back into the OUTLET BOX
  - 3, Screw the TOP LOOP to the NIPPLE, Place the CANOPY against the OUTLET BOX, and secure it with the TOP NUT.
  - 4, Put the GLASS onto the SOCKET AND screw with the METAL RING and SOCKET RING
  - 5, Install bulbs. (Please do not exceed the maximum capacity which is recommended on the sockets).
- INSTALLATION COMPLETE. Turn on the power at fuse or circuit box.

