

ASSEMBLY INSTRUCTION



- Before assembly, please put on the white gloves inside the box.
- During the second step, please pay attention to the direction of Part B (Seat Cushion) and Part D (Mechanism), which you can judge by the "Front" tags. The tilt tension knob should be in the front and the height control lever on your right when sitting down.
- Do not tighten the screws one by one. Try to align them first and tighten a few screws slightly. Then align the rest again and tighten them all.
- Because of the weight of the seat and backrest, sometimes it might be easier to assemble when putting one side of the chair on the ground.

1

Diagram 1 shows the base plate (G) being attached to the casters (H) using screws (F). The screws (F) are shown being inserted into the base plate (G) from the top. The casters (H) are shown attached to the bottom of the base plate (G).

2

Diagram 2 shows the backrest (B) being attached to the mechanism (D) using screws (K) and a pin (M). The screws (K) are shown being inserted into the backrest (B) from the top. The pin (M) is shown being inserted into the mechanism (D) from the side.

3

Diagram 3 shows the seat cushion (C) being attached to the mechanism (D) using screws (J) and a pin (M). The screws (J) are shown being inserted into the seat cushion (C) from the top. The pin (M) is shown being inserted into the mechanism (D) from the side.

4

Diagram 4 shows the armrests (A) being attached to the seat cushion (C) using screws (L) and washers (N). The screws (L) are shown being inserted into the armrests (A) from the top. The washers (N) are shown being inserted into the seat cushion (C) from the top.

5

Diagram 5 shows the assembled seat being placed on the base plate (G). The seat is shown being lowered onto the base plate (G).

6

Diagram 6 shows the fully assembled office chair. The chair is shown in a side view, with the seat, backrest, armrests, and base plate (G) all attached.

A		1
B		1
C		2
D		1
E		1
F		1
G		1
H		5
I	M6*20	4
J	M6*30	8
K	Diameter=16mm	4
L		8
M		1
N	Diameter=13mm	8