



## Ozone Generator Instruction Manual

### Product Parameters

**Ozone Output:** 30,000mg/hour

**Power Gears:** Low (10,000mg/h) / Medium (20,000mg/h) / High (30,000mg/h)

### Applicable Space:

Low Gear: ≤500 sq.ft.

Medium Gear: 501-1,500 sq.ft.

High Gear: 1,501-2,000 sq.ft.

**Product Size:** 15cm×10cm×8cm

**Net Weight:** 0.5kg

### Detailed Explanation of Core Functions

#### Intelligent Power Adjustment System

#### Gear Corresponding Scenarios:

Low Gear: Odor removal for closed small spaces such as cars, wardrobes, and pet nests

Medium Gear: Daily living areas like kitchens, bathrooms, and bedrooms

High Gear: Heavy odor scenes such as basements, smoking rooms, and garbage rooms

**Adjustment Method:** Short-press the power button to cycle through gears, and the corresponding gear indicator light will turn on.

#### Delay Fan Cleaning System

**Operation Mechanism:** The fan continues to run for 60 seconds after the device automatically shuts down.

#### Core Functions:

Blow away condensed water on the surface of the ozone tray

Remove adsorbed dust particles

Experimental data shows it can extend the device's service life by 20%.

#### Detailed Use Process

##### Operation Steps

#### Boot Preparation:

Place the device in a well-ventilated area (≥10cm away from the wall)

Connect to the power supply, and the power indicator light will turn on.

#### Gear Setting:

Short-press the power button to select the gear according to the space area (refer to "Product Parameters")

It is recommended that the high gear does not run for more than 30 minutes at a time.

#### Operation and Shutdown:

The device will automatically shut down after running for 60 minutes by default

Long-press the power button to force shutdown.

#### Ventilation Treatment:

Open doors and windows immediately after shutdown for ventilation

For living environments, it is recommended to ventilate for ≥30 minutes

For closed spaces (such as cars), ventilate for ≥15 minutes.

#### Safety Precautions

#### Personnel Protection:

Personnel must evacuate the use space during operation

Allergic individuals are advised to extend ventilation to 1 hour.

#### Equipment Maintenance:

Wipe the ozone tray with a dry cloth monthly

Do not rinse the body with water directly.

#### Prohibited Scenarios:

Do not operate in environments with people, animals, or plants

Avoid long-term use in humid environments (humidity >80%).

#### Exception Handling:

If abnormal noise or odor occurs, cut off the power immediately

For equipment failures, please contact after-sales service

