



### A20-087

### **4 IN 1 SLEEPING AND CAMPING SET**



## **OWNER'S MANUAL**

READ AND FOLLOW ALL INSTRUCTIONS BEFORE USING THIS PRODUCT. SAVE THESE INSTRUCTIONS.



Thank you for using GOLEADER 4 in 1 sleeping and camping set. Our mission is to design and manufacture the finest products with materials of the highest quality and production process in order to meet your demands. You can visit the retailer or our website for other fine GOLEADER products.



- 1. The campiing bed should be assembled and disassembled by adults only.
- 2. Children should be supervised at all times.
- 3. Do not install or use the camping bed under adverse weather conditions such as rain, hail, sleet, snow, drizzle, lightning, strong wind, etc.
- 4. Place the camping bed on a solid and level ground.
- 5. Keep away from fire and heat sources.
- 6. To avoid finger entrapment, assemble and disassemble the camping bed carefully.
- 7. The camping set is designed for a maximum load of 450 lbs (204 kg). Do not overload and do not use the camping bed single.
- 8. Do not jump on the camping bed. This is not a trampoline.
- 9. Make sure the camping bed is dry before storing in a safe place indoors.

# TO AVOID PROPERTY DAMAGE OR SERIOUS INJURY, FOLLOW ALL THESE INSTRUCTIONS.


#### PARTS REFERENCE:

NOTE: Illustrations are for your reference only. It may not reflect the actual product.



REF. NO.	QUANTITY	DESCRIPTION	REF. NO.	QUANTITY	DESCRIPTION
A-1	1	Camping bed (two bars included)	A-6	1	Pump
A-2	1	Airbed	A-7	4	FRP pole
A-3	1	Cushion cover			
A-4	1	Tent wall			
A-5	1	Junction cross			

NOTE: Be careful during the assembly process, or you may get hurt. Make yourself familiar with the assembly process.




1. Unfasten the velcro straps and put aside the two bars.



2. Unfold the legs of the camping bed and stand them on a solid & level ground.



3. Expand the legs.



4. Align a bar and insert it into the bed sleeve.




7. Insert another bar on the opposite bed sleeve and repeat step 4-6.



5. Stick the bend joint of the bar onto the middle frame of the camping bed.



8. Spread out the airbed on the camping bed. Then inflate the airbed with a hand pump.NOTE: Do not over inflate.



6. Fasten the bar.



9. Coat the airbed with the cushion cover and fasten the velcro straps.



10. Put 4 leng poles into tent, then Take out the FRP poles. Insert the to the junction cross into 2 holes of the camping bed diagonally.Make sure the marking "A" points to the bedhead.Then separately insert one end of the residual FRP poles into the residual holes of the camping bed and the other end into the junction cross.