

Assembly & Installation Instructions

PREPARATION before INSTALLATION:

1. If an existing fixture is being replaced, remove it and note to which wire in the outlet box the original fixture was attached.
2. Before discarding the carton, double-check the packaging to make sure all parts have been found.
3. This fixture was designed to be mounted on an octagon outlet box. The box must be securely mounted to the structure of the building.

IMPORTANT:

1. **WARNING** - Disconnect power before relamping or wiring the fixture. Turn off the entire electrical circuit to which the lighting fixture is attached.
2. Installation and maintenance of this fixture should be completed by a licensed electrician.
3. Failure to install the fixture correctly could result in serious injury or death.
4. Read all instructions before starting installation.

INSTALLATION STEPS:

1. Align the mounting bracket with the junction box holes, mark and drill the holes, insert the wall anchors.
2. Secure the mounting bracket to the junction box with screws, and tighten it onto the wall anchors by using the self-tapping screws.
3. Connect the wires by using the wire caps as follows:
Connect the fixture's LIVE (BLACK) wire to the home LIVE wire.
Connect the fixture's NEUTRAL (WHITE) wire to the home NEUTRAL wire.
Connect the fixture's ground wire to the home ground wire.
Secure the fixture's ground wire to the mounting bracket with the green grounding screw.
Then, tuck all wires into the junction box.
Note: make sure no bare wires are exposed to prevent electric leakage.
4. Position the light fixture upward and align it with the holes on the mounting bracket.
5. Secure the light fixture to the mounting bracket with screws.
6. Install the acrylic diffuser inside the lampshade. (When adjusting it, fit it closely to the inner height of the lampshade's bottom), and position it properly.

