



General Information

Material number

Type	pendant light
Product segment	Indoor
Theme	sonstige / nicht zuordenbar

Dimensions

Article Height (in mm)	1100
Article Width (in mm)	100
Article Length (in mm)	710
Net Weight (in kg)	0.73 Kilogram
Article Diameter (in mm)	100
Base Diameter (in mm)	645
Article Overhang (in mm)	75
Canopy Height (in mm)	25
Canopy Diameter (in mm)	105
Canopy Length (in mm)	710
Canopy Width (in mm)	48
długość podstawy(w mm)	70
Szerokość podstawy (w mm)	70
Installation Depth (in mm)	115
Cutout (in mm)	79

Material & Colour

Enclosure Material	steel
Enclosure Colour	satin nickel
Glass/Shade Material	glass vaporized
Glass/Shade Colour	gold color
Cable Colour	transparent

Functionality

Switch Type	without switch
Battery	No
Function	remote control incl. LED not replaceable control via remote control CCT
Kąt czujnika (in °)	150
Czułość min. (w lux)	10
Czułość maks. (w lux)	200
Burning Time min. (in sec.)	5
Burning Time max. (in sec.)	900
Distance (in Meter)	12
Battery Type	AAA; R03P; 1,5V

Technical Information

Protection Degree	IP20
Protection Class	2
Mains Voltage	220-240V,50/60Hz
Operation Voltage	220-240V,50/60Hz
max. Wattage (1)	1X15W
Dimmable	No
max. Wattage (2)	1X18W

Illuminant 1

Illuminant Type (1)	E27
Illuminant incl. (1)	Exclusive
Socket Type (1)	E27

Illuminant 1

Socket Type (1)	GU10
Illuminant Type (1)	GU10-LED
Illuminant incl. (1)	Inclusive
Energy efficiency class (EEI)	F
Info changeability□light source/driver	LED exchangeable by customers, no driver included

Illuminant 1

Socket Type (1)	LED
Illuminant Type (1)	LED
Illuminant incl. (1)	Inclusive
Lumen Complete	630
Kelvin Complete	3000K
Light colour Complete	WARM WHITE
Energy efficiency class (EEI)	F
Dimmable	No
Info changeability□light source/driver	LED + driver can be exchanged by a specialist
Nominal Lifetime (in h)	25000
Switching Cycles	15000
Rated Lamp Power (0,1W precision)	24,5
Colour Tolerance (LED, SDCM)	<6
lumen z osłoną	110

Illuminant 2

Socket Type (2)	LED
Illuminant Type (2)	LED
Illuminant incl. (2)	Inclusive
Lumen Complete	920;400
Kelvin Complete	3000K
Light colour Complete	WARM WHITE;WARM WHITE
Dimmable	No
Info changeability□light source/driver	LED + driver can be exchanged by a specialist

Illuminant 2

Illuminant Type (2)	E14-ILLU
Illuminant incl. (2)	Exclusive
Socket Type (2)	E14

