



Catalog Number
Notes
Type

Contractor Select™

IBE ALO

LED High Bay

The right selection for your basic, affordable warehouse lighting – the IBE ALO luminaire gives budget-conscious customers a reliable LED solution. The IBE ALO is designed to meet the challenges of warehouse and light industrial applications.

FEATURES:

- CSA listed to 40°C ambient
- Save up to 60% in energy and maintenance costs over traditional sources
- Compact 18" housing



Catalog Number	UPC	Description	Lumens	Input Watts	CCT	CRI	Voltage	Distribution	Pallet Qty.
IBE AL021 MVOLT SWW9 80CRI DWH	00196183778918	IBE LED Switchable High Bay	12000/16000	92/133	4000/5000K	80CRI	120-277V	Medium	112



Specifications

INTENDED USE:

Ideal one-for-one replacement of conventional lighting systems such as HID and fluorescent. For use in light Industrial applications such as warehousing and other large indoor spaces with mounting heights ranging from 10' - 18' permitted. **Certain airborne contaminants can diminish integrity of acrylic and/or polycarbonate.** [Click here for Acrylic-Polycarbonate Compatibility table for suitable uses.](#)

Certain airborne contaminants may adversely affect the functioning of LEDs and other electronic components, depending on various factors such as concentrations of the contaminants, ventilation, and temperature at the end-user location. [Click here for a list of substances that may not be suitable for interaction with LEDs and other electronic components.](#)

CONSTRUCTION:

Solid steel channel and aluminum reflector channel enables superior thermal performance at warm ambient temperatures.

Frosted semi-diffuse, acrylic lens provides glare control and LED protection.

ELECTRICAL:

70% lumen maintenance at >50,000 hours.

Thermally protected driver standard. Luminaire Surge Protection Level: Designed to withstand up to 2.5kV/3kA per ANSI C82.77-5-2015.

INSTALLATION:

Fixture suitable for suspension or surface surface mount. One pair of 36" long chain hangers and a surface-mount bracket are included with fixture. To maintain ambient listing, fixture should be mounted at a minimum plenum height of 18".

LISTINGS:

CSA listed. Damp location listed. Listed for use in ambient operating temperatures from -20°C to 40°C. Thermal management system allows for safe operation during times when temperatures rise to 45°C*.

WARRANTY:

2-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:

www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. The product images shown are for illustration purposes only and may not be an exact representation of the product.

Specifications subject to change without notice.

Dimensions

All dimensions are inches (centimeters) unless otherwise indicated.

