

FLUSH MOUNT

- Die Cast Aluminum
- Size options between 4.75", 6.25", 8.5", and 10.5"
- Ultra-thin 1/2" height with less than 1/4" trim
- Available in 3000k (Made-to-order Color Temperatures available)
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in White (WT), Black (BK), Polished Chrome (PC) and Satin Nickel (SN)
- Dimmable with Triac and ELV Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box (pancake and mud ring acceptable)
- Pendant light accessory available (sold separately)
- Suitable for Wet Location, for use on ceilings outdoor and above showers
- ETL/cETL IP65




Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



PENDANT ACCESSORY
 (Sold Separately,
 Fixture NOT included)

PRODUCT DESCRIPTION

Thin discs of evenly illuminated LED create the impression of recessed lighting. The die-cast aluminum housings are available in White, Black, Satin Nickel, and Polished Chrome all with a thoughtfully recessed White polycarbonate diffuser. High efficiency and good color rendering make this a perfect choice for your next project. Use the optional pendant adapter to convert any size to a hanging fixture.



MEASUREMENTS

DIMENSION	CANOPY	WIRE LENGTH
4.75"W x 0.75"H x 4.75"L	4.5"D x 0.5"H	8"L
6.25"W x 0.75"H x 6.25"L	6"D x 0.5"H	8"L
8.5"W x 0.75"H x 8.5"L	8.25"D x 0.5"H	8"L
10.5"W x 0.75"H x 10.5"L	10.25"D x 0.5"H	8"L
2.25"W x 10.75"H x 2.25"L, 120"OAH	5"W x 0.25"H x 5"L	120"L

LAMPING

BULB TYPE	CRI	COL TEMP.	LUMENS RATED	DEL	DIMMABLE	INPUT
12.5W PCB LED (Integrated)	90+	3000K	920	875	Triac CL	120V
15W PCB LED (Integrated)	90+	3000K	1100	1050	Triac CL	120V
18W PCB LED (Integrated)	90+	3000K	1280	1260	Triac CL	120V
20W PCB LED (Integrated)	90+	3000K	1450	1400	Triac CL	120V

FINISHES OPTIONS:

- Polished Chrome (PC)
- Satin Nickel (SN)
- White (WT)
- Black (BK)



MATERIAL:

PC + Aluminum
 Shade: Polycarbonate

GLASS:

White Acrylic (WT)

AVAILABLE SIZE:

4.75" | 6.25" | 8.5" | 10.5"

RATINGS:

cETLus
 Wet Location
 Dimmable
 Title 24 JA8 Compliant
 Energy Star
 ADA



ADDITIONAL:

RATED LIFE: 35,000 hours
 WARRANTY: 5 Years

Always consult a qualified electrician before installing any lighting product