Ρ	roj	ec	t:

Fixture Type:

Location:

Contact:

LED Wall Mount • Wet Location



Specifications:

Description:

These series are ideal for a wide variety of interior and exterior applications including residential and commercial. The Cylinders feature a 120V alternating current source and eliminates the need for a traditional LED driver. This modular approach results in an encapsulated luminaire that unites performance, cost and safety benefits.

2

120V

60Hz

3000K

-30° C

30° C

5 yrs.

90

29W per module

60,000 (L70/TM-21)

FCC Title 47, Part 15, Class B

cCSAus certified for wet locations

2000/68 (LM-79) PER MODULE

Construction:

Performance: Number of Modules

Input Power

Input Voltage

Lumens/LPW

CCT

CRI

Life

EMI/RFI

Warranty

Labels

Min. Start Temp Max. Operating Temp

Input Frequency

- Powdercoated Antique Bronze, White, Black, Metallic Gray
- Die-cast aluminum construction
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- · Covers a standard 4" recessed outlet box
- $\boldsymbol{\cdot}$ Mounting strap for outlet box included

Images:



Dimensions:



Catalog number:

Finish	Color Temp	CRI
Antique Bronze	3000K	90 CRI
White		
Black		
Metallic Gray		



Dimming Notes:

It is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls. The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.