INSTALLATION INSTRUCTIONS



INSTALL EASY CONNECT MOUNTING BRACKET:

Easy Connect

mounting

bracket

SAFETY PRECAUTIONS:

1.TURN OFF ELECTRICAL POWER BEFORE STARTING INSTALLATION OF LIGHT FIXTURE.

2. THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

NOTE: Product May Not Look Exactly As Shown In Figures.



Option 2 - MULTIPLE ELECTRICAL BOX WIRES



For multiple black (live) & white (neutral) wires joined in the electrical box (house wiring), attach a single "black" and "white" Jumper Wire before connecting. Strip 7mm from a 6" Jumper Wires (AWG 12-24) supplied. Then connect (push) wires into correct inserts.

Box White (Neutral) Green (Ground) Black (Live)

CONNECT HOUSE WIRES STEP 2 - Option 1

STEP 1

Electrical



CONNECT LIGHT FIXTURE STEP 3



Connect (push) electrical wires from fixture into correct inserts. Black (live), White (neutral), Green (ground)

Connect (push) electrical

wires from electric box

inserts. Black (Live),

White (Neutral),

Green (Ground)

Attach easy connect

to electrical box with

electrical box screws (not included).

mounting bracket

STEP 4



Tuck electrical wires into outlet box and position fixture over studs or nipple on mounting bracket assembly. Secure fixture in place with star washer(s) and cap nut(s). Note: If required, assemble body and spread the arms of the fixture out evenly.

STEP 5



After Installation, seal around the top and side perimeter between the fixture and the wall surface with weather resistant caulking. The bottom should be left un-caulked to prevent moisture build-up. Apply a small amount of weather resistant caulking around the side perimeter between the cap nut and mounting plate.

STEP 6 - Optional for some models (Note: Refer to the style of assembly that matches the style of your fixture.)



STYLE#1 - Install proper bulb type and wattage. Slide the glass down.



STYLE#2 - Install proper bulb type and wattage. Unscrew glass cylinder to install bulb. Screw glass cylinder back on to the fixture.