WARNING

(To reduce the risk of fire,electrie shock,or injury to persons):

1.We suggest installation by a licensed electrician.

2.Please read the instruction carefully and save it as you may need it at later time.

3.Before you start,NEVER attempt any work without shutting off the electricity until the work is done.A). Go to the main fuse,or circuit breaker,box in your home.Place the main power switch in the "OFF"position.B) Place the wall switch in the "OFF"position.

4.Mounting surface should be clean,dry,flat,strong enough and 1/4"larger than the canopy on all side. Any gaps between the mounting surface and canopy exceeding 3/16"should be corrected as required.

5.Make sure that the ceiling or wall can bear the weight of the lamp before fixture.

6.Make sure the voltage you are using is 120V.The maximum wattage is 60W per bulb.

7.Keep the lamp away from acidic objects in case of damaging the surface of the lamp.

8.When replacing bulb,you should turn off or unplug the lamp and you must wait until it is cool as bulbs get hot quickly.

9.The safety instructions appearing in this manual are not meant to cover all possible conditions that may occur.

It must be understood that common sense,caution and care must be used with any electrical products.

10.Do not touch the bulb or lamp shade during the lighting fixture working.

Image for finished product:




Accessories List :



Screw  Screw gasket  Wire connector



Electric wire current lead  Tool  Instruction

## Installation Procedures:

### First:

A) Open the package and take out all the parts or accessories, then place them on a clean flat place.
B) Please turn off the power.




| Connect Black or Red Supply Wire to: | Connect White Supply Wire to: |
|---|---|
| Black | White |
| *Parallel cord (round & smooth) | *Parallel cord (square & ridged) |
| Clear, Brown, Gold or Black without tracer | Clear, Brown, Gold or Black with tracer |
| Insulated wire (other than green) with copper conductor | Insulated wire (other than green) with silver conductor |

*Note: When parallel wires (SPT I & SPT II) are used. The neutral wire is square shaped or ridged and the other wire will be round in shape or smooth (see illus.)







Please install according to the picture with the text description.

1. Attach the branch pole to the light arm.
2. Loosen the screws of the lamp body.
3. Splicing the light body together.
4. Install the light body to the mounting bracket.
5. Lock the bracket onto the junction box.
6. Connect the live wire (L), zero wire (N) and ground wire (E) to the junction box.
7. Use the black nut to lock the lamp body on the mounting bracket.
8. Adjust the lamp body and tighten the screws of the lamp body.
9. Use the lamp head ring to lock the glass shade on the light fixture.
10. Install the E26 light bulb.

**If you need any help, please contact us.**