


### Hardware Package (included):



Cross Bar (A)



Mounting Screw (B)



Head Screw (D)



Lock Nut (E)



Wire Nut (F)



Ball Nut (G)

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

**WARNING:** TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

NOTES: 1. Before installing, consult local electrical codes for wiring and grounding requirements.  
2. READ AND SAVE THESE INSTRUCTIONS.

## Installation Steps

Turn off the power at fuse or circuit box

### Assembly of the fixture body

Step:01. Screw the lamp arm into the connector

Step:02. Insert the lamp arm tube into the hole of the back plate (pay attention to protect the cap wire from being damaged). Screw the lamp arm tube with lock nut(E)

### Installation Instructions

Step:03. Attach the cross bar to the outlet box by using two mounting screws(B).

Step:04. Pull out the source wires from the outlet box. Make wire connections using wire nuts(F) as follows:

---Connect the hot wire (usually black insulation) from the fixture to the black wire from the power source.

---Connect the neutral wire (usually white insulation) from the fixture to the white wire from the power source.

---Attach the fixture grounding wire (usually bare wire) connect it to the house grounding wire with the wire nut.

--- Carefully put the wires back into the outlet box.

Step:05-06. Attach the fixture body to the cross bar by inserting headless screws into holes on back plate, and then secure it with two rubber pads and two ball nuts(G).

Step:07. Install E26 bulb (not included). Check relamping label at socket area or packaging for maximum allowed wattage.

## Attention

1. Due to the different display, the actual color can be different from the image
2. Due to the manual measurement of lamp body size, there may be a deviation of 1 / 2 inch
3. If you have any questions or lost parts, please feel free to contact us and we will try our best to help you

