

# WAC LIGHTING

## Twist-N-Lite

### Flush Mount

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
FM-250905	CS 2700K/3000K/3500K/4000K/5000K - 90	10W	660	BK Black BN Brushed Nickel WT White

Example: **FM-250905-CS-BK**

#### DESCRIPTION

Quick and convenient. Easy to use and easy to install, our new Twist-N-Lite system offers a variety of surface mounts and pendant luminaires in five color temperatures and three finishes. A single flexible mounting base accommodates our complete suite of Twist-N-Lite products. The flexible design enables you to interchange the fixtures in the field to meet your various lighting applications. This energy-efficient engineering wonder offers dimmable options for high performance and a classic, minimalistic aesthetic. Select your color temperature, Twist it in and Turn it on. Elevating multifunctional illumination to a higher standard.

#### FEATURES


- Mount and power any fixture in the Twist-N-Lite family by twisting it onto the canopy
- All wiring and connections are made in the junction box prior to installing the mounting base and canopy
- Shared canopy allows for easily swapping between fixtures without adjusting the mounting hardware
- 5-CCT Switchable between 2700K and 5000K
- Dual-layer acrylic for frosted and even glow
- Driver concealed within the fixture
- 5 year warranty

#### SPECIFICATIONS

<b>Construction</b>	Aluminum with dual-layer acrylic diffuser
<b>Power:</b>	10W
<b>Input:</b>	120 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-10% , TRIAC: 100-10%
<b>Light Source:</b>	Integrated LED
<b>Lens:</b>	Dual-layer acrylic diffuser
<b>Rated Life:</b>	50,000 Hours
<b>Mounting:</b>	Installs over a 3", 4" or 3/0-4/0 hybrid junction box, Can be mounted on ceiling or wall in all orientations
<b>Finish:</b>	Electrostatically Powder Coated: Black, Electroplated Brushed Nickel, White
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	ETL, cETL, Wet Location Listed, ADA, Title 24 JA8 Compliant



#### FINISHES:



#### LINE DRAWING

