Outdoor Wall Sconce 3000K

Size	Color Temp & CRI		Finish		Watt	LED Lumens	Delivered Lumens	Title 24
12"	3000K	90	BK	Black	9.5W	800	213	Yes
	3000K	90	BZ	Bronze	9.5W	800	213	Yes

_____   _____

• For 277V special order, add an "F" before the finish: WS-W48625F-BZ

DESCRIPTION

A design with solid casted aluminum that shelters an advanced LED light engine within the inner chamber to provide maintenance-free illumination for many years. Chamber features a collection of wet location listed wall sconces, pendants, and post lights for consistency in design throughout any project.

FEATURES

• Minimal mounting hardware for easy installation
• Light engine is factory sealed for maximum protection from the elements
• Weather resistant powder coated finish
• ACLED driverless technology
• 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%
Rated Life:	50000 Hours, 44000 Hours
Mounting:	Can be mounted on wall vertically or upside down
Standards:	ETL, cETL, IP65, Title 24: 2016, Dark Sky Friendly
	Wet Location Listed
Construction:	Aluminum hardware with etched glass lens

FINISHES

Black   Bronze

Outdoor Wall Sconce 3000K

Size	Color Temp & CRI		Finish		Watt	LED Lumens	Delivered Lumens	Title 24
16"	3000K	90	BK	Black	12W	1000	255	Yes
	3000K	90	BZ	Bronze	12W	1000	255	Yes

• For 277V special order, add an "F" before the finish: WS-W48625F-BZ

DESCRIPTION

A inspired design with solid casted aluminum that shelters an advanced LED light engine within the inner chamber to provide maintenance-free illumination for many years. Chamber features a collection of wet location listed wall sconces, pendants, and post lights for consistency in design throughout any project.

FEATURES

• Minimal mounting hardware for easy installation
• Light engine is factory sealed for maximum protection from the elements
• Weather resistant powder coated finish
• ACLED driverless technology
• 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%
Rated Life:	50000 Hours, 44000 Hours
Mounting:	Can be mounted on wall vertically or upside down
Standards:	ETL, cETL, IP65, Title 24: 2016, Dark Sky Friendly
	Wet Location Listed
Construction:	Aluminum hardware with etched glass lens

FINISHES

Black   Bronze

Outdoor Wall Sconce 3000K

Size	Color Temp & CRI		Finish		Watt	LED Lumens	Delivered Lumens	Title 24
- 20"	3000K	90	BK	Black	18W	1600	519	Yes
	3000K	90	BZ	Bronze	18W	1600	519	Yes

• For 277V special order, add an "F" before the finish: WS-W48625F-BZ

DESCRIPTION

A inspired design with solid casted aluminum that shelters an advanced LED light engine within the inner chamber to provide maintenance-free illumination for many years. Chamber features a collection of wet location listed wall sconces, pendants, and post lights for consistency in design throughout any project.

FEATURES

• Minimal mounting hardware for easy installation
• Light engine is factory sealed for maximum protection from the elements
• Weather resistant powder coated finish
• ACLED driverless technology
• 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%
Rated Life:	50000 Hours, 44000 Hours
Mounting:	Can be mounted on wall vertically or upside down
Standards:	ETL, cETL, IP65, Title 24: 2016, Dark Sky Friendly
	Wet Location Listed
Construction:	Aluminum hardware with etched glass lens

FINISHES

Black   Bronze

Outdoor Wall Sconce 3000K

Size	Color Temp & CRI		Finish		Watt	LED Lumens	Delivered Lumens	Title 24
- 25"	3000K	90	BK	Black	22W	1800	605	Yes
	3000K	90	BZ	Bronze	22W	1800	605	Yes

_____   _____

• For 277V special order, add an "F" before the finish: WS-W48625F-BZ

DESCRIPTION

A inspired design with solid casted aluminum that shelters an advanced LED light engine within the inner chamber to provide maintenance-free illumination for many years. Chamber features a collection of wet location listed wall sconces, pendants, and post lights for consistency in design throughout any project.

FEATURES

• Minimal mounting hardware for easy installation
• Light engine is factory sealed for maximum protection from the elements
• Weather resistant powder coated finish
• ACLED driverless technology
• 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%
Rated Life:	50000 Hours, 44000 Hours
Mounting:	Can be mounted on wall vertically or upside down
Standards:	ETL, cETL, IP65, Title 24: 2016, Dark Sky Friendly
	Wet Location Listed
Construction:	Aluminum hardware with etched glass lens

FINISHES

Black   Bronze