

## SCHEDULE 8

## Product information

## Product information sheet

1. The product information sheet must contain the information set out in Table 6.

Table 6

## Product information sheet

|  |  |  |  |
|--|--|--|--|
| Supplier's name or trade mark: <b>Impex Lighting Limited</b>   |  |  |  |
| Supplier's address: Impex House, Wellington Road, London Colney, St Albans, AL2 1EY  |  |  |  |
| Model identifier: <b>LED608242/01/CH</b>   |  |  |  |
| Type of light source: <b>LED</b>   |  |  |  |
| Lighting technology used:  | [HL/LFL T5 HE/LFL T5 HO/CFLni/other FL/HPS/MH/other HID/ <b>LED</b> /OLED/mixed/other] | Non-directional or directional:  | [ <b>NDLS</b> /DLS]                          |
| Light source cap-type (or other electric interface)  | [Free text]  |  |  |
| Mains or non-mains:  | [MLS/ <b>NMLS</b> ]  | Connected light source (CLS):  | [yes/ <b>no</b> ]                            |
| Colour-tunable light source:   | [yes/ <b>no</b> ]  | Envelope:  | [ <b>no</b> /second/non-clear]               |
| High luminance light source:   | [yes/ <b>no</b> ]  |  |  |
| Anti-glare shield:   | [yes/ <b>no</b> ]  | Dimmable:  | [yes/only with specific dimmers/ <b>no</b> ] |
| Product parameters   |  |  |  |
| Parameter  | Value  | Parameter  | Value  |
| General product parameters   |  |  |  |
| Energy consumption in on-mode (kWh/1,000 h) rounded up to the nearest integer  | <b>6</b>   | Energy efficiency class  | [A/B/C/ <b>D</b> /E/F/ G]                    |
| Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | x in [ <b>sphere</b> /wide cone/narrow cone]   | Correlated colour temperature, rounded to the nearest 100K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set | [x/x...x/x or x (or x...)]                   |

|   |              |  |  |
|---|--------------|--|--|
| On-mode power (Pon), expressed in W   | <b>6</b>     | Standby power (Psb), expressed in W and rounded to the second decimal point                              | <b>0.4</b>   |
| Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal point  | <b>N/A</b>   | Colour rendering index, rounded to the nearest integer, or the range of CRI_x0002_values that can be set | <b>85</b>  |
| Outer dimensions without separate control gear, lighting control parts and non_x005f_x005f_x005f_x005f_x002_lighting control parts, if any (millimetre) | Height       | /  | Spectral power distribution in the range 250 nm to 800 nm, at full_x005f_x005f_x005f_x002_load |
|   | Width        | /  |  |
|   | Depth        | /  |  |
| Claim of equivalent power (see paragraph [2(1) and (2)])  | [yes/no]     | If yes, equivalent power (W)   | x  |
|   |              | Chromaticity coordinates (x and y)   | <b>0.388</b><br><b>0.377</b>   |
| Parameters for directional light sources:   |              |  |  |
| Peak luminous intensity (cd)  | <b>N/A</b>   | Beam angle in degrees, or the range of beam angles that can be set                                       | [x/x...x]<br><b>N/A</b>  |
| Parameters for LED and OLED light sources:  |              |  |  |
| R9 colour rendering index value   | <b>5</b>     | Survival factor  | <b>0.90</b>  |
| The lumen maintenance factor  | <b>0.96</b>  |  |  |
| Parameters for LED and OLED mains light sources:  |              |  |  |
| Displacement factor (cos φ1)  | <b>0.7</b>   | Colour consistency in McAdam ellipses  | <b>4</b>   |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage (see paragraph [2(3)]).          | [yes/no]     | If yes then replacement claim (W)  | x  |
| Flicker metric (Pst LM)   | <b>0.359</b> | Stroboscopic effect metric (SVM)   | <b>0.015</b>   |

