

Ravello Floor

astro

General

Location:	Interior
Class:	cULus (Class I)
Location Rating:	Dry
Driver Required:	Mains 120V
Installation Orientation:	-
Fitting Method:	-
Main Material:	Metal - Mild Steel
Dimensions (mm):	H: 1585 W: 290 D: 225
Dimensions (inch):	H: 62.4 W: 11.42 D: 8.86
Cut Out Hole (mm/inch):	-
Recess Depth (mm/inch):	-
Fire Rating:	-
Cable Length (mm/inch):	2250/88.58
Gross Weight (lb):	20.24
Ada Compliant:	Yes - if installed in compliance with ADA 308, 309.3, 309.4
Ic Rating:	-

Lamp

Light Source:	E26/Medium
Wattage:	25W Max
Lamp Included:	No
Maximum Lamp Length (mm/inch):	190/7.48
Luminous Flux (lm):	Lamp Dependent
Colour Temp (K):	Lamp Dependent
Cri (Ra):	Lamp Dependent
Macadam Ellipse:	-
Tilt Adjustable Angle (°):	-
Rotation Adjustable Angle (°):	-
Average Lifetime (hrs):	Lamp Dependent
Beam Angle (°):	-

Electrical

Switched:	Yes
Dimmable:	-
Dimming Method:	-
Supply Frequency (Hz):	-
Driver/Ballast Voltage (V):	-
Driver Average Lifetime (hrs):	-
Efficacy (lm/W):	Lamp Dependent

Additional Information:

Shade Included:	Shade Sold Separately
Shade/Diffuser Material:	-
Shade/Diffuser Finish:	-
F Mark:	-



CODE: 1222076
FINISH: BRONZE



CODE: 1222083
FINISH: MATT BLACK



CODE: 1222084
FINISH: MATT NICKEL



CODE: 1222085
FINISH: POLISHED CHROME

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under u.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

With Drum 420 Shade

