

ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

1. Shut off the power at the circuit breaker and remove existing fixture, including the mounting hardware.
2. Screw out the screw and take out the mounting plate from the fixture.
3. The pendant fixture is adjustable at the time of installation. Use a small screwdriver (provided) to adjust the required length.
4. After placing mounting plate on the wall to position two holes, drill two 1/4" holes, then insert Plastic wall anchor into 1/4" hole.
5. Run the wire through the center wire hole on the mounting plate
6. Twist together white fixture wire, marked with white tape with white outlet wire. Next, twist together black fixture wire with black outlet wire. Use wire nuts to secure connection. Connect the fixture ground wire to the outlet box ground wire using wire nut (not provided).
7. Use the mounting plate to the outlet box using the strap mounting screw, and then lock the wood screw to the plastic wall anchor.
8. Push from plate to ceiling, Carefully push the screws through the side holes in the canopy and lock them onto the mounting plate.
9. Insert fabric shade into lamp holder and fasten with socket ring.
10. Install the bulb (not included). Please follow the wattage label located on the fixture body.
Do not exceed the recommended wattage.

