

Project:

Fixture Type:

Location:

Contact:

Ceiling stem mounted • Dry location listed



Description:

Uniquely shaped modern LED mini-pendant with sleek lines. This pendant utilizes a Brushed Nickel Finish with a white linen interior for optimal light output.

Specifications:

- Brushed Nickel (plated)
- Steel construction metal
- Dimmable (See Dimming Notes)
- Canopy covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied
- ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	121171.2 (LM-79)
CCT	3000 K
CRI	90
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30
Max. Operating Temp	
Warranty	5 year warranty
Labels	cCSAus Dry location listed
	ENERGY STAR® qualified

Images:



Dimensions:

Diameter: 10"  
Height: 10-3/4"  
Overall Ht. W/Stem: 77"



### Dimming Notes:

---

This collection is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls.

### Dimming Controls

---

Lutron DVELV-300P

Lutron NTELV-300

Lutron VTELV-600

Lutron MAELV-600

Lutron SPELV-600

Leviton 6615-P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.