



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-1603 - 2X2 LED Single Basket Troffer; Emergency Battery; Field Selectable; 120-277 Volt; White Finish

- Wattage Selectable
- Has Emergency Battery
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	20W/30W/40W
Volts:	120V-277V
Lumens:	2500L/3750L/5000L
Lamp Base :	Integrated - Integrated
CRI:	80+
CCT (Kelvins):	35K/40K/50K - Neutral White to Natural Light
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
Incandescent Equivalent :	200W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Connection:	Hardwire
Surge Protection :	Built-in surge protection - 2KV
THD:	<20%
Power Factor :	0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923516030
Each Quantity:	1
Each Dimensions:	24.61 x 1.77 x 24.33

PHYSICAL

Finish:	White
Lens Finish:	White
Lens Material:	Polycarbonate (PC)
Dimensions:	L:23.74" W:23.74" H:1.62"
Weight (Lbs.):	9.48
Material:	Steel
Panel Size:	2x2

COMPLIANCE

Safety Listing:	cULus - Certified
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Premium; Premium
DLC ID:	S-0TM900; S-B6YMG0
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP20
RoHS Compliant:	Yes
Restrictions:	No Restrictions



65-1603 - 2X2 LED Single Basket Troffer; Emergency Battery; Field Selectable; 120-277 Volt; White Finish

DIMMER COMPATIBILITY

Legrand	ADPD4FBL3P2W4
Legrand	CD4FBLW
Eaton	DF10P
Leviton	DS710-10Z
Lutron	DVSCSTV
Lutron	DVSTV
Leviton	IP710-LFZ
Lutron	MS-Z101
Lutron	MS-Z101-V
Lutron	NFTV
Lutron	NTSTV-DV
Legrand	RH4FBL3PTCCCV6
Lutron	RMJS-8T-DV-B + PJ2-3BRL-GWH-L01