

SLSTP Series - LED Striplights

Suspension or surface mount, seamless lens for sleek appearance



Now available in 2', 4', and 8' lengths with up to 11K lumens with 3500K and 4000K options in stock. The SLSTP is a fully integrated LED solution that offers improved performance at value driven pricing. This LED strip is easy to install, seamless, with impact resistant lens and continuous row mount capability.



Targeted at distributor day-to-day stock requirements and design build projects, the SLSTP is an ideal replacement for any traditional fluorescent striplight application.



Construction and Performance

- 8', 4', and 2' lengths with single lens (no tandem)
- Excellent performance - up to 125 lm/W and 10,500 lumens
- Simple sensor options on 4' and 8' lengths
- Frost polycarbonate lens, linear prisms for even illumination
- UNV, 0 to 10V or 120V, Phase Cut dimming
- Two CCT: 3500K and 4000K
- Row-mount accessory snaps in to create straight rows and speed installation
- J-Box cover and decorative endcaps included

Reliability and Compliance

- TM21 rated at L70 at 50,000 hrs.
- LED modules comply with IESNA LM-79 and LM-80 standards
- DesignLights Consortium® Qualified for all models
- ENERGY STAR® certified for 120V models
- cULus listed 1598 for damp locations
- Five-year comprehensive warranty

Model #	Product Description	LED		Compared to T12 Fluorescent		Compared to T8 Fluorescent	
		Lumens	Wattage	Fixture Wattage	Energy Savings	Fixture Wattage	Energy Savings
2SLSTP1040DD-120V	2ft. LED Striplight, 120V	1250	11	20	45%	17	35%
2SLSTP2040DD-120V	2ft. LED Striplight, 120V	2510	23	43	47%	32	28%
4SLSTP2040DD-120V	4ft. LED Striplight, 120V	2579	23	43	47%	32	28%
4SLSTP4040DD-120V	4ft. LED Striplight, 120V	4474	40	70	43%	56	29%
2SLSTP2040DD-UNV ¹	2ft. LED Striplight, UNV	2510	23	43	47%	32	28%
4SLSTP4040DD-UNV ¹	4ft. LED Striplight, UNV	4760	44	70	38%	56	22%
4SLSTP5540DD-UNV ¹	4ft. LED Striplight, UNV	5845	49	88	44%	70	30%
8SLSTP8040DD-UNV ¹	8ft. LED Striplight, UNV	8176	71	169	58%	113	37%
8SLSTP11040DD-UNV ¹	8ft. LED Striplight, UNV	10464	83	192	57%	141	41%
4SLSTP4040CS	Sensor + 4ft. LED Striplight, UNV	4835	41	70	41%	56	27%
8SLSTP8040CS	Sensor + 8ft. LED Striplight, UNV	8304	72	169	57%	113	36%

¹ Performance shown in 4000K CCT, also available with the 3500K



Powering Business Worldwide

Eaton
1121 Highway 74 South
Peachtree City, GA 30269
P: 770-486-4800
www.eaton.com/lighting

Canada Sales
5925 McLaughlin Road
Mississauga, Ontario L5R 1B8
P: 905-501-3000
F: 905-501-3172

© 2018 Eaton
All Rights Reserved
Printed in USA
Publication No. SA502045EN
February 13, 2018

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Product availability, specifications, and compliances are subject to change without notice.