

PROJECT INFORMATION		
JOB NAME		TYPE
ORDERING CODE		

OUTDOOR QB

Up and Down IP65 Wall

85° BEAM		
(Note: Specifications are subject to change without notice)		
14mm COB PERFORMANCE DATA		
LED LIGHT ENGINE	NOMINAL DELIVERED LUMENS	SYSTEM WATTAGE
05LM	300LM @30K/90CRI	9.6W
Notes	2x9.6W, 150lm up, 150lm down. Delivered lumens based on standard reflector.(see page 2)	



FEATURES

- Pre finish anodizing process for corrosive-inhibiting protection
- 2 Finish options: Anthracite or Silver
- 3000K or 4000K CCT options
- IP65 Rated

DIMMING AND CONTROLS

- 0-10V dimming

CONSTRUCTION

- Extruded aluminum housing
- Anodized and powder coat finish
- Mount to 3-1/2" to 4" octagonal or 4" square recessed junction box

LED

- LED: Zigen ZG6CGD34Z0S
- SDCM: 3-step MacAdam Ellipse
- Lumen Maintenance: $L_{70} > 50,000$ hrs


LISTING

- ETLus Listed to UL1598 (suitable for wet locations)
- cETL Listed to CSA C22.2 #250.0
- Warranty: 5 year limited warranty
- BUG Rating: B1 - U1 - G
- 3000k or warmer must be selected for International Dark-Sky Association approval

ELECTRICAL

- 120V-277V
- Ambient operating temperature -20°C/-4°F to +40°C/+104°F

WALL



PROJECT INFORMATION		
JOB NAME		TYPE
ORDERING CODE		

BEAM ORDERING CODE											
SERIES	EXT	exterior									
TYPE	QB	QB up and down, 9.6W									
LED	SW	standard white									
DELIVERED LUMENS	05LM	300 lm, 150 lm Up / 150 lm Down									
	Standard Configuration: 3000K Calculated Delivered Lumens = [Delivered Lumen Value] x [CCT Multiplier] x [Optic Multiplier]										
CCT	30K	3000K									
	40K	4000K									
		<table border="1"> <thead> <tr> <th>CCT</th> <th>3000K</th> <th>4000K</th> </tr> </thead> <tbody> <tr> <td>CRI</td> <td>90</td> <td>90</td> </tr> <tr> <td>CCT MULTIPLIER FOR LUMEN OUTPUT</td> <td>1</td> <td>1.1</td> </tr> </tbody> </table>	CCT	3000K	4000K	CRI	90	90	CCT MULTIPLIER FOR LUMEN OUTPUT	1	1.1
CCT	3000K	4000K									
CRI	90	90									
CCT MULTIPLIER FOR LUMEN OUTPUT	1	1.1									
CRI	90	90 CRI									
FINISH	BK	anthracite									
	SV ¹	silver									

BEAM ORDERING CODE		
MOUNTING OPTIONS	W	wall mount
VOLTAGE	UNV-10V	120V-277V integrated driver, flicker free 0-10V dimming to 10%

YOUR COMPLETED ORDERING CODE	
Follow the steps to specify your fixture, example:	
EXT - QB - SW - 05LM - 30K - 90 - BK - W - UNV-10V	

NOTES

1. Silver only offered in 3000K and non-dimmable.

