


Examine all packaging material for small parts that may have come loose during shipment. Periodic checks are recommended to insure that all components are in proper position, tight and free from damage. Keep this assembly instruction for future reference. Adult assembly is required.

HARDWARE LIST

- A (16) 1/4" x 15mm Allen Bolts
- B (4) 1/4" x 25mm Counter Bolts
- C (2) 1/4" x 18mm Counter Bolts
- D (4) 1/4" x 25mm Allen Bolts
- E (20) 6.5mm Spring Washers
- F (20) 6.5mm Flat Washers
- G (1) Allen Wrench

PARTS LIST

- H (1) Seat Back
- I (1) Seat
- J (1) Stool Base
- K (4) Legs
- L (1) Top Support
- M (1) Lower Support

PART	QTY	HARDWARE
A	16	
B	4	
C	2	
D	4	
E	20	
F	20	
G	1	

STEP 1

Begin assembly by attaching 2 Legs (K) to the bottom of the Stool Base (J) using 2 Allen Bolts (A), 2 Spring Washers (E) & 2 Flat Washers (F) to secure in place. Do not fully tighten bolts for this step.

STEP 2

Next, attach the Top Support (L) to each mounted Leg (K) using 1 Counter Bolt (B) from the inside. Also attach the Lower Support (M) to the bottom inside of each mounted Leg using 2 Allen Bolts (A), 2 Spring Washers (E) & 2 Flat Washers (F) to secure in place.

STEP 3

Repeat Steps 1 & 2 to assemble the remaining 2 Legs (K) and secure to Top & Lower Supports (L & M). Completely tighten all bolts using Allen Wrench (G) provided.

STEP 4

Attach the Stool Back (H) to the Seat (I) by fitting in place and securing with 1 Counter Bolt (C) per each bottom side. Tighten all bolts using Allen Wrench (G) provided.

STEP 2

Attach the Seat (I) to the Stool Base (J) by aligning the holes with the swivel metal plate and securing the bottom with 4 Allen Bolts (D), 4 Spring Washers (E) & 4 Flat Washers (F) to secure in place. Tighten all bolts using Allen Wrench (G) provided.

