

Item 1692

LAGUNA

Showerhead & Hand Shower

Designed in Italy



5 Settings



To Install

1. Remove existing showerhead from Shower Arm. Clean shower arm thread.
2. Wrap teflon tape (included) around shower arm thread to prevent leakage.
3. Hand tighten Shower Arm Mount to Shower Arm.
4. Hand tighten Shower Hose Nut to Shower Arm Mount, other end of Shower Hose to handle.
5. Place handle onto Mount by sliding its handle with attached hose nut into Holder.

To Use

Turn On water and select desired water pattern by turning Dial Lever.

To adjust Mount angle, loosen Holder Nut, rotate Holder into desired position and tighten Holder Nut to lock position.

Installation Aids

1. Pliers or wrench may help to untighten your old showerhead and tighten connections. Do not use wrench or pliers on plastic parts.
2. Tighten all connections well. Check position of washers if leakage occurs between connections. Use teflon tape on male threads if leakage still occurs.
3. Irregular shower arms that do not have shower thread, require an adapter available at most plumbing retailers, or you can replace your shower arm with standard 1/2" thread shower arm. Old shower arm can be easily replaced by simply unscrewing it and screwing in new shower arm in its place (pliers or wrench may be required).



TEN YEAR LIMITED WARRANTY

Interlink will repair or replace any of this product's parts that exhibit defects in workmanship or materials for above stated period from date of purchase. If malfunction occurs, send only defective part(s) with proof of purchase to Customer Service Department at the address listed below. Your warranty does not cover malfunction or damage due to accident, misuse, use of harsh chemicals or failure to follow any written instructions accompanying this product. This warranty does not cover product purchased from unauthorized distributors. This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

Cleaning Instructions

Do not use harsh chemicals or abrasives that may damage finish. Such damage is not covered by product warranty. To clean mineral deposits, spray or soak nozzles with shower cleaner or household vinegar.

**For installation help
or part replacement,
call Toll Free 1-888-869-4010**

Imported

Interlink Products International, Inc.
1315 E. Elizabeth Ave., Linden, NJ 07036

A112.18.1 Maximum Flow 2.5 Gallons Per Minute 9.5 Liters Per Minute