

Туре Suspension Light



Dimensions

S1 cone: Ø150 × H210mm S2 round: Ø150 × H210mm S3 cone: Ø300 × H205mm

Canopy Dimensions Ø150mm × H82mm

Wiring Type Mains voltage

Types of Insulation Class III (3)

Ingress Protection Rating IP20

Voltage 110/120V AC, 60Hz

Packaging Dimensions

S1 cone: L300mm x W240mm x H90mm S2 round: L300mm x W240mm x H90mm S3 cone: L390mm x W320mm x H100mm

Weight S1 cone: 1.25kg S2 round: 1.25kg S3 cone: 1.70kg

Packaging Type Carton (external), styropor (internal)

205 Ø300

> Weight 0.85kg 0.85kg 1.10kg

Cable Length L2000mm

Dimmable Mains dimmable

Light Source Supplied No

Light Source Type LED (recommended)

Light Source Base F12

Care & Maintenance

Clean with a soft dry cloth.

Do not use alcohol, polishes,

the material. This product is

suitable for indoor use only.

for continuous use over 16h.

the product, as they may damage

Protect against exposure to heat

above 60°C. Not recommended

Notes

This product is fitted with E12 light source fittings. Established abrasives or any solvents to clean & Sons recommend using this product with E12 (max. 6W) LED light sources. Established & Sons will not accept any responsibility for any accidents, injuries or damages that occur due to the use of incorrect light sources.

Country of Origin China

Certifications



Design 2008 Designer Sylvain Willenz

With its tactile, silicone the Torch Light reveals its references to the shape and material of the typical torch, while the diamond-textured diffuser cleverly references the glass of a car headlight. It's easy to create a fun, vibrant look by combining different colours and sizes within the same space or to state your style by choosing the Torch Light bunch, an ultra-modern feature chandelier. Heroic in black or red, lively and fun in yellow, bespoke drop heights provide architecturally bold pieces for double or triple height ceiling spaces.

Materials

Power (Watts)

Light Source Lumens

Light output will vary depending

on the type of light source used in

the luminaire. Recommended max.

Max. 6W

800lm.

Compression-moulded Silicone shade and ceiling fixture, clear diamond textured polycarbonate diffuser, fabric covered cable



Light Source Colour Temperature

Levels will vary depending on the type of light source used in the luminaire. Recommended 2700K LED light source.

ablished