LED Wall Mount · Wet Location

Specifications:

Description:

This product features a 120V alternating current (AC) source which eliminates the need for a traditional LED driver.

Construction:

- Powdercoated Solid Copper (-14), Gilded Iron (-71), Antique Nickel (-81)
- Die-cast aluminum construction
- LED Module is replaceable (part # 93053641)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- CA Title 24 Compliant
- Covers a standard 4" recessed outlet box
- Mounting strap for outlet box included

Images:

Performance:

|	
Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1211/71 (LM-79)
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 yrs.
Labels	cCSAus certified for wet locations ENERGY STAR® qualified

Dimensions:

A	B
12"	12-1/4"

Extends	H/CTR
13-1/4"	6-7/8"

Catalog number:

Base	-	Finish	Color Temp	CRI
		14 - Solid Copper	30K - 3000K	9 - 90 CRI
		71 - Gilded Iron		
		81 - Antique Nickel		

Dimming Notes:

This product is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase)
controls. The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.