


99406

PESCAITO



General Information

Material number	99406
Type	wall / ceiling light
Product segment	Indoor
Theme	sonstige / nicht zuordenbar
FSC®	FSC® Mix70% Pinus rad. FSC® C152762

Dimensions

Article Height (in mm)	65
Article Length (in mm)	490
Net Weight (in kg)	0.4 Kilogram
Article Overhang (in mm)	75
Article Width (in mm)	490
Article Diameter (in mm)	280
Canopy Length (in mm)	530
Canopy Width (in mm)	45
Canopy Height (in mm)	25
Base Diameter (in mm)	220
Base Length (in mm)	230
Base Width (in mm)	150
Installation Depth (in mm)	26
Cutout (in mm)	205
Canopy Diameter (in mm)	300

99406

PESCAITO

Material & Colour

Enclosure Material	steel
Enclosure Colour	black
Glass/Shade Material	plastic
Glass/Shade Colour	white, gold
Cable Colour	black

Functionality

Switch Type	without switch
Battery	No
Function	LED not replaceable control via wall switch CCT
Battery Type	AAA; R03P; 1,5V
Sensor Angle (in °)	120
Sensitivity min. (in lux)	30
Burning Time min. (in sec.)	5
Burning Time max. (in sec.)	15
Distance (in Meter)	6

Technical Information

Protection Degree	IP20
Protection Class	1
Mains Voltage	220-240V,50/60Hz
Operation Voltage	220-240V,50/60Hz
max. Wattage (1)	10W
Dimmable	No
Spannung	220-240V 50/60Hz
U out	46-70V
I out	300mA
Hz	100Hz
max. Wattage (2)	10W
max. Wattage (3)	8W
max. Wattage (4)	6W
max. Wattage (5)	4,4W

Illuminant 1

Illuminant Type (1)	E27
Illuminant incl. (1)	Exclusive
Socket Type (1)	E27

Illuminant 1

Socket Type (1)	LED
Illuminant Type (1)	LED
Illuminant incl. (1)	Inclusive
Kelvin Complete	3000K
Light colour Complete	WARM WHITE
Nominal Lifetime (in h)	25000
Switching Cycles	15000
Energy efficiency class (EEI)	F
Dimmable	No
Info changeability□light source/driver	LED + driver cannot be exchanged
Rated Lamp Power (0,1W precision)	36
Colour Tolerance (LED, SDCM)	<6
Lumen Complete	1100

Illuminant 1

Socket Type (1)	GU10
Illuminant Type (1)	GU10-LED
Illuminant incl. (1)	Inclusive
Energy efficiency class (EEI)	F
Info changeability□light source/driver	LED exchangeable by customers, no driver included

Illuminant 2

Socket Type (2)	LED
Illuminant Type (2)	LED
Illuminant incl. (2)	Inclusive
Lumen Complete	2300;1500;1150
Kelvin Complete	3000-6500K
Light colour Complete	TUNEABLE WHITE;TUNEABLE WHITE
Dimmable	No
Info changeability□light source/driver	LED + driver can be exchanged by a specialist

Illuminant 3

Socket Type (3)	LED
Illuminant Type (3)	LED
Illuminant incl. (3)	Inclusive
Lumen Complete	2300;1500;1150
Kelvin Complete	3000-6500K
Light colour Complete	TUNEABLE WHITE;TUNEABLE WHITE
Energy efficiency class (EEI)	E
Dimmable	No
Info changeability□light source/driver	LED + driver can be exchanged by a specialist

99406

PESCAITO

