



2X2 LED Panel by WENLIGHTING

- Available Wattage: 40W
- Color Temperature Available: 4000K
6500K & 5000K
- Luminous Flux Available: 4000 Lumens
- Beam angle: 120°
- Lifespan: 50,000 hours
- Voltage: AC100-277V
- IP40 Rated
- Working Temp. : -4°F to 113°F
- Dimension : 23.74x23.74
- ETL certified.
- Dimming: 0-10V/PMW/Resistant dimming
- 5 years warranty



LED Panel 2X2 lights need no introduction. Because of its tasteful design, good energy saving capacity and less maintenance cost, they have become a suitable replacement for fluorescent and incandescent bulbs. If you are planning to redo your hotel's interior, you can pick these lights to accentuate the looks of the reception area. These sleek and suave lights are also fit for medical and health institutions.



SPECIFICATION

MPN	Model Name	Wattage	Voltage	Lumens	CCT	Beam Angle	CRI
PN021	WEN-CPS-U4A40-P6-5000K	40	100-277V	4000	5000K	120°	>82
PN022	WEN-CPS-U4A40-P6-4000K	40	100-277V	4000	4000K	120°	>82
PN019	WEN-CPS-U4A40-P6-6500K	40	100-277V	4000	6500K	120°	>82



MODEL VARIATION



- LED ceiling lights can be installed in four ways-built in, recessed, mounted and suspended. Built-in and recessed installation offers the sleeker look, albeit the latter provides the subdued lighting.
- With high CRI- colors pop, textures stand out and finishes have depth and luster. Sleek and suave, Led panel lights have 80 + CRI, which means when you put a yellow colored object under this light you see it as yellow.



WARNING AND CAUTIONS

- The product must be installed according to the instructions. Installed by a person familiar with the product, production and product hazards.
- Avoid fire and electric shock. When installing the lighting fixtures, you need to understand the electrical characteristics. If you are not sure, do not attempt to install. Please contact an electrician.
- Understand the structural features and dimensions of lighting before installation.



502-303-4518



Info@wenlighting.com



www.wenlighting.com