



General Information

Type	ceiling light
Product segment	Indoor
Theme	sonstige / nicht zuordenbar
FSC®	FSC® Mix70% Hevea br FSC® C152762

Dimensions

Article Height (in mm)	150
Article Length (in mm)	690
Net Weight (in kg)	1.08 Kilogram
Article Overhang (in mm)	120
Article Width (in mm)	280
Article Diameter (in mm)	380
Canopy Length (in mm)	530
Canopy Width (in mm)	45
Canopy Height (in mm)	25
Base Diameter (in mm)	645
Base Length (in mm)	230
Base Width (in mm)	150
Installation Depth (in mm)	26
Cutout (in mm)	205
Canopy Diameter (in mm)	460

Material & Colour

Enclosure Material	steel, aluminium
Enclosure Colour	black
Glass/Shade Material	plastic
Glass/Shade Colour	white
Cable Colour	black

Functionality

Switch Type	without switch
Battery	No
Function	LED not replaceable
Battery Type	CR2032
Sensor Angle (in °)	120
Sensitivity min. (in lux)	30
Burning Time min. (in sec.)	5
Burning Time max. (in sec.)	15
Distance (in Meter)	6

Technical Information

Protection Degree	IP20
Protection Class	1
Mains Voltage	220-240V,50/60Hz
Operation Voltage	24V
max. Wattage (1)	19W
Dimmable	No
Spannung	220-240V 50/60Hz
U out	46-70V
I out	300mA
Hz	100Hz

Illuminant 1

Illuminant Type (1)	E27
Illuminant incl. (1)	Exclusive
Socket Type (1)	E27

Illuminant 1

Socket Type (1)	LED
Illuminant Type (1)	LED
Illuminant incl. (1)	Inclusive
Kelvin Complete	3000K
Light colour Complete	WARM WHITE
Nominal Lifetime (in h)	25000
Switching Cycles	15000
Energy efficiency class (EEI)	E
Dimmable	No
Info changeability□light source/driver	LED + driver can be exchanged by a specialist
Rated Lamp Power (0,1W precision)	36
Colour Tolerance (LED, SDCM)	<6
Lumen Complete	2700

Illuminant 1

Socket Type (1)	GU10
Illuminant Type (1)	GU10-LED
Illuminant incl. (1)	Inclusive
Energy efficiency class (EEI)	F
Info changeability□light source/driver	LED exchangeable by customers, no driver included

