



Highline® | K-44199

Elongated toilet bowl

Features

- Elongated bowl offers added room and comfort
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults
- 2" (51 mm) fully glazed trapway
- Revolution 360® flushing technology generates a forceful swirling motion to keep the bowl clean longer
- Weighs less than previous Highline models
- Combines with a K-44470, K-44468, or K-44467 tank
- Replaces Highline® K-4199 bowl



Available Colors/Finishes

Color tiles intended for reference only.

	0	White
	96	Biscuit
	7	Black Black



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.

7-30-2026 06:12 - US-CA

THE BOLD LOOK
OF **KOHLER**®

Codes/Standards

Accessibility standards may require controls to be located on the open side of the toilet.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

ASME A112.19.2/CSA B45.1

Technical Information

Rough-in:	Standard 12" (305mm)
Flush Type:	Revolution 360
Flush Rate:	1.28 gpf
Bowl Shape:	Elongated
Seat-Mounting Holes:	5-1/2" (140 mm)
Waste Outlet:	Floor
Trapway Size:	2-1/8" (54 mm)
Trapway Type:	Exposed
Water Surface Size:	8" x 8" (203 mm x 203 mm)
Rim to Water Surface:	6-9/16" (166 mm)

Recommended Products/Accessories

K-44467 Toilet tank, 1.28 gpf

K-44467-RA Toilet tank, 1.28 gpf

K-44467-U Toilet tank, 1.28 gpf

K-44467-UR Toilet tank, 1.28 gpf

K-23726 Drain treatment

Warranty

See website for detailed warranty information.

KOHLER® Toilets and Seats Limited Warranty



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.

7-30-2026 06:12 - US-CA

No image available.

This product is a component and not intended to be a standalone installation.

Installation

- Standard 12" (305 mm) rough-in

Installation Notes

Install this product according to the installation instructions.

Product dimensions are nominal and may vary per ASME A112.19.2 tolerances.

