

Assembly Instruction Sheet

Go to the **Care + Maintenance** selection.

Tools Required: Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.

Light Source: LED 15W

Compatible Dimmer Switches: Lutron DVELV-300P or Lutron SELV-300P.

Estimated Assembly Time: 20-30 minutes


Preparation: Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

⚠ Warnings and Cautions

Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt.

These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation.

Package Contents



STEP 3 - Wire Connections

- Wrap bare or green ground wire around green ground screw on the crossbar, no less than 2 inches from the end of the wire. Tighten the green ground screw.
- Use standard wire connectors (not included) to make all wire connections. Twist connectors until wires are tightly joined together. Wrap each connection with approved electrical tape and carefully stuff all the connected wires into the Outlet Box.




Figure 3

STEP 1 - Adjust the Fixture Body Height

- Loosen the set screw on the rope clamp by using a screwdriver.
- Adjust the cord length to achieve your desired fixture height. Move the slider on the cord until it is next to the hex nut inside of the ceiling canopy.
- Keep excess cord inside the ceiling canopy.




Figure 1

STEP 4 - Attach Ceiling Canopy to Crossbar

- Line up the holes on the side of the ceiling canopy to the mounting holes on the Crossbar (A). Secure them with Mounting Screws (B). Tighten until snug.

Your fixture is now assembled and ready to use. Enjoy!




Figure 4

STEP 2 - Attach Crossbar to Outlet Box

- Attach the Crossbar (A) to outlet box and secure by threading outlet box screws (not supplied) into the mounting holes on the outlet box. Tighten until snug.






Figure 2

Thank you for purchasing a product.

NOTE: ALL DIMENSIONS ARE ROUNDED UP TO THE NEAREST 1/4"

FINISH: POLISHED CHROME



Thank you for purchasing a product.